

Industrial vacuum cleaner 55 S


Dry vacuum cleaner useful in most applications with dust from tools or cleaning operations within industry



The 55S is a efficient three phase compact industrial vacuum cleaner. A very efficient, economical, low noise level and easy to handle dry vacuum. The vacuum is very easy to dismantle and clean. This portable dust collector has long filter lifetime 4-6000 h (with bag filter). The location of the (optional) micro filter prevents contamination of the pump. The forward/reverse switch saves time when moving between work sites with different phase sequence.





- Long filter lifetime (4-6000 hours)
- Low noise level
- Micro filter as option

Product name	Industrial vacuum cleaner 55 S
Noise level (dB(A))	72
Protection class	IP 55
Filter efficiency (%)	99
Installation	Indoor
Material	Casing in sheet metal
Filter cleaning method	Reverse air pulse
Application	Dust, Granulate, Fumes, Chip
Working pressure (in. wg)	30
Dustbin volume (gal)	7,3
Max Airflow (cfm)	210
Hose Diameter (in)	2,01
Hose length (ft.)	16,4 ft
No of phases	3
Filter type	Bag
Number of filter elements	1
Filter material	Polypropylene
Noise level (dB(A))	72
Weight (lbs)	223
Hose length (m)	16,4
Hose diameter (mm)	2



Granulate Fumes Chip Dust


Industrial vacuum cleaner 55 S

Image	Power Voltage (V)	Frequency (Hz)	Max vacuum (in. wg)	Power (Hp)	Model
	400	50	120	7.4 (5.5 Kw)	40056000*
	230	60	-118	8.4 (6.3 Kw)	40056030*
	460	60	-118	8.4 (6.3 Kw)	40056040*
	400	50	120	7.4 (5.5 Kw)	40056060**

*Heavy duty cleaning equipment included

**Heavy duty cleaning equipment included. Antistatic filter and micro filter included

Industrial vacuum cleaner 55 S

	Accessory	Part No
	Microfilter D= 140 x 500	40114120
	Hand nozzle, hard brush Ø90mm, Ø51	43860001*
	Hand nozzle, soft brush Ø90 mm	43860200*
	Toothed nozzle width 130 mm, Ø51	43861001**
	Cone nozzle Length 250 mm, Ø51	43862001**
	Scraper nozzle, length: 1000 mm Ø51	43851150**
	Scraper nozzle, length: 500 mm Ø51	43851050**
	Bulk nozzle Length 910 mm, Ø51	43850001*
	Bulk nozzle for floor with handle length 1200 mm, Ø51 mm	43850150**
	Filter candle set, Polypropylene, E+B245efficiency (EN60335-2-69): L	40114180
	Filter candle set, PTFE, Efficiency (EN60335-2-69): M	40114440
	Filter candle set , Antistatic, Efficiency (EN60335-2-69): L	40114190
	Collection bin liner (plastic, 1/ea)	40376934

*ATEX - Suitable for combustible dust with MIE (minimum ignition energy) < 1mJ. Ensure earthing to extraction unit. Not to be used in combustible gas atmospheres or extraction of explosive materials

**ATEX - Suitable for combustible dust (zone 20,21,22) and gas (zone 1,2) of group IIA , IIB and IIC. Ensure earthing to extraction unit. Not to be used for extraction of explosive materials