

Exhaust Hose Reel 865 - Electric Motor Driven

Electric Motor Driven Exhaust Hose Reel




The best solution in workshops with a high ceiling, where overhead cranes etc. have to be considered, or where high vehicles must pass. Operated via a hand unit either an IR control or pendant control. A receiving eye on the reel shows the status of operation. Electronic upper and lower limit switches reduce the risk of malfunction and unnecessary wearing of the hose. Fan start/stop is automatically controlled. Mounting of fan on reel is possible. No programming is lost when a power failure occurs. If the power is cut, the electro-magnetic brake will lock the drum instantly.

- Convenient and safe operation
- Automatic Fan for energy savings
- Quick & easy installation reduces cost
- Settings for limit switches made from floor level
- Compact, modern design

Product name	Exhaust Hose Reel 865 - Electric Motor Driven
Installation	[Indoor]
Material recycling (% weight)	100
Operating Temperature	14 - 122 F (-10 to +50 C)
Further technical data	Max lifting capacity: 30kg Power supply: 325 VA
Power Voltage (V)	100-230
Frequency (Hz)	50/60
No of phases	1
Colour	Blue
Body type	[wide]
Electric/Spring driven	[ElectricMotor]



Exhaust Hose Reel 865 - Electric Motor Driven

[image]	Type of hose ¹	Delivered with hose	Diameter, hose (in)	Hose length (ft)	Weight (lbs)	Max hose length	[model]
			4	25	90 - 108	41	20802965
			5	33	90 - 108	33	20803365
			6	16	90 - 108	33	20803965
			4	33	68	41	20802665*
			5	49	68	33	20802765*
			6	41	68	33	20802865*
			8		68	23	20809165**
							89299121
							89299126
							89298143
							86900525






*Delivered without hose.

**Max hose length 22 ft coiled, Max weight of hose including nozzle 65 lbs.

¹ See table below

Hose type	Specification	Temperature range, °C	Hose fittings in free hose end, distribution hose	Hose fitting on free hose end, inlet hose	Hose connection on reel, distribution hose	Hose connection on reel, inlet hose
NRCP		-40 to +150 Deg. C (Intermittent +170 Deg. C)				

Exhaust Hose Reel 865 - Electric Motor Driven

	[accessory]	[partno]
	Pendant control incl. cable bracket	20373712
	Transmitter with wall bracket	20373522
	Direct mount bracket for fan on 865 Hose Reel	20373556
	Transformer 230/250 V to 24 V. 75 VA.	10361560
	Transformer 230/250 V to 24 V. 25 VA.	10363189
	8in Clip Grip/Bridge Hose Clamp	87000934
	Flex Noz 6"complt w 9"opening2007en	89298063
	Flex Noz 6"complt w 8"opening2007en	89298058
	Bracket to mount 8" hose reel on Extension Arm	86900229
	Stainless Steel Nozzle for 5" hose with locking clamp & lifting sleeve	89298082
	NFC-4.2 Hose Ex 100mm/5 m	86900683
	Flex Noz 6"complt w10"opening2007en	89298062

Exhaust Hose Reel 865 - Electric Motor Driven

