Nederman

Exhaust Nozzles

High temperature resistant rubber and metal exhaust hoses



Nederman offer an extensive range of robust rubber and metal vehicle exhaust extraction nozzles to accommodate various types of vehicles and systems including European standard EURO 6 engines. Adjustable test funnels with special design to handle large volumes of hot exhaust from vehicles in inspection centres for example. Also available with floor stand and for vertical exhaust pipes. The adjustable floor stand accommodates most exhaust pipe positions and designs.

- Easy manual connection and disconnection of the exhaust nozzles
- Well proven nozzles with a soft capturing hood that protects employees and vehicles
- The nozzles are resistant to high exhaust temperature up to 150°C (300°F) for rubber nozzles and up to 400°C (750°F) for metal nozzles, in normal use.

| Product name | Exhaust Nozzles |
|--------------|-----------------|
| Installation | [Indoor] |



| [image] | Description | Max exhaust pipe, diameter. Dual (mm) | Vehicle type | Max exhaus pipe, single (mm) | Hose connection Diameter (mm) | [model] |
|---------|--|--|--------------|---------------------------------|----------------------------------|----------|
| | Rubber nozzle with lid and metal hose | n.a. | | 150 | 100 | 20803161 |
| | Rubber nozzle with lid and metal hose | n.a. | | 150 | 125 | 20803261 |
| | Rubber nozzle with lid and metal hose | n.a. | | 150 | 150 | 20803361 |
| | Rubber nozzle, triangular, Spring-loaded lid, wire guard and opening for CO probe | 100 x 75 | | 75 | 75 | 20803461 |
| | Rubber nozzle, triangular, Spring-loaded lid, wire guard and opening for CO probe | 100 x 75 | | 75 | 100 | 20803561 |
| | Rubber nozzle, triangular, Spring-loaded lid, wire guard and opening for CO probe | 100 x 75 | | 75 | 125 | 20803661 |
| 4 | Rubber nozzle, triangular with lid | 100 x 75 | | 75 | 75 | 20804061 |
| 4 | Rubber nozzle, triangular with lid | 100 x 75 | | 75 | 100 | 20804161 |
| 4 | Rubber nozzle, triangular with lid | 100 x 75 | | 75 | 125 | 20804261 |
| | Exhaust Nozzle Rubber Ø100 (4") Manual Triangular. With metal hose. | 100 x 75 | | 75 | 100 | 20322139 |
| | Exhaust Nozzle Rubber Manual With metal hose | n.a. | | 150 | 150 | 20322140 |
| -4 | Rubber nozzle, oval, opening for CO probe. Hose connection angled 60 deg. | 150 x 75 | | 75 | 75 | 20805461 |
| -4 | Rubber nozzle, oval, opening for CO probe. Hose connection angled 60 deg. | 150 x 75 | | 75 | 100 | 20805561 |
| - | Rubber nozzle, round, with wireguard | n.a. | | 150 | 150 | 20805961 |
| | Rubber nozzle, oval for variable pipe thickness | 150 x 75 | | 75 | 100 | 20808361 |



| [image] | Description | Max exhaust pipe, diameter. Dual (mm) | Vehicle type | Max exhaus pipe, single (mm) | Hose connection Diameter (mm) | [model] |
|---------|--|--|--------------|---------------------------------|----------------------------------|----------|
| | Rubber nozzle, oval, opening for CO probe. Hose connection angled 60 deg. | 200 x 100 | | 100 | 125 | 20805661 |
| | Rubber nozzle, oval, opening for CO probe. Hose connection angled 60 deg. | 200 x 100 | | 100 | 150 | 20805761 |
| 6 | Rubber nozzle, round, with wireguard CO probe. Hose connection angled 60 deg. | n.a. | | 150 | 125 | 20805861 |
| | Rubber nozzle, oval, automatic wire release | 150 x 75 | | 75 | 100 | 20806161 |
| Ĉ | Rubber nozzle,round, automatic wire release | n.a. | | 150 | 125 | 20806461 |
| | Rubber nozzle, round, automatic wire release | n.a. | | 150 | 150 | 20806561 |
| Ó | Rubber nozzle, round, swivel and lengthwise compressible | 240 x 230 | | 180 | 150 | 20806961 |
| Ó | Rubber nozzle, round, swivel and lengthwise compressible | 240 x 230 | | 230 | 200 | 20807061 |
| | Rubber nozzle, oval, Spring-loaded lid, wire guard and opening for CO probe. Without locking clamp | 150 x 110 | | 110 | 100 | 20802561 |
| * | Rubber nozzle, with safety disconnection, automatic release | n.a. | | 150 | 150 | 20807861 |
| | Aluminium nozzle with wire guard | n.a. | | 125 | 150 | 20804761 |
| | Aluminium nozzle with wire guard | n.a. | | 170 | 200 | 20804961 |
| | Rubber nozzle . Slips on to the exhaust pipe without locking device | | | 100 | 75/100 | 20815261 |
| | Rubber nozzle . Slips on to the exhaust pipe without locking device | | | | 100 | 20817261 |
| | Beak nozzle | | | 100 | 100 | 20866461 |



| [image] | Description | Max exhaust pipe, diameter. Dual (mm) | Vehicle type | Max exhaus pipe, single (mm) | Hose connection Diameter (mm) | [model] |
|----------------------|--|--|--------------|---------------------------------|----------------------------------|----------|
| | Beak nozzle | | | 75 | 75 | 20866561 |
| | Beak nozzle | 150 x 80 | | 125 | 150 | 20866661 |
| | Beak nozzle | 150 x 80 | | 125 | 125 | 20866761 |
| | Beak nozzle | 150 x 80 | | 125 | 100 | 20866861 |
| | Beak nozzle | 150 x 80 | | 125 | 75 | 20866961 |
| | Nozzle for built-in and covered exhaust pipes. Internal grip. | 240 x (35 - 70) | | 70 | 100 | 20867261 |
| | Nozzle for built-in and covered exhaust pipes. Internal grip.Includes quick coupling | 240 x (35 - 70) | | 70 | 100 | 20867661 |
| | Nozzle for built-in and covered exhaust pipes. Internal grip and extension hood (270mm). | 270 x (35 - 70) | | 70 | 100 | 20867861 |
| | For Cars with twin pipes. | 250 x 80 | | | 100 | 20867761 |
| | Rubber funnel on floor stand. Height 0 - 600 mm, rotatable | | | | 100 | 20868361 |
| Carity - | Funnel on floor stand with wheels. Height 0 - 600 mm, rotatable | | | | 150 | 20816861 |
| • | Nozzle on floor stand. Height 130 - 440 mm | | | | 200 | 20807261 |
| 00 1 | Large aluminum generic funnel. Suitable for EURO 6 trucks. With high temperature resistant kevlar based hose. | | | | 150 | 20817061 |
| 0 C | Aluminum funnel incl. With high temperature resistant kevlar based hose. | | | | 150 | 20817161 |
| 90 90 90 90 | Flexible stand for funnels 20817061 , 20817161 and nozzle 20817261. | | | | 75 | 20816961 |



| [image] | Description | Max exhaust pipe, diameter. Dual (mm) | Vehicle type | Max exhaus pipe, single (mm) | Hose connection Diameter (mm) | [model] |
|------------|---|--|--------------|---------------------------------|----------------------------------|--------------|
| | Galvanised steel nozzle for stack pipes, length 2600 mm | n.a. | | 250 | 140 | 20801961 |
| | Rubber nozzle for vertical stack | n.a. | | 250 | 125/150/200 | 20808861 |
| | Galvanized nozzle for vertical stacks | n.a. | | 250 | 150 | 20816661 |
| <u>I</u> T | Galvanized nozzle for vertical stacks | n.a. | | 250 | 200 | 20816761 |
| •• | Nozzle for exhaust Pipe internal size 140 x 58mm | | | | 100 | 20869761* |
| | Nozzle for exhaust Pipe internal size 175 x 60mm | | | | 100 | 20869861** |
| • | Nozzle for exhaust Pipe internal size 126 x 80mm | | | | 100 | 20869961*** |
| 9 : | Nozzle for exhaust Pipe internal size 175 x 85mm | | | | 100 | 20870061**** |

*For Mercedes C, Mercedes CLA, Mercedes E GLE and Ford Mondeo 2015.

**For Audi A6 2015 and Citoën DS
***For Volvo XC60, V60 and S60 (Before 2015), Mercedes R, GLK and GLA 2015, Mercedes E (Before 2013) and Porsche Cayenne.
****For Volvo S60, S90, S60 cross country (From 2015), V40, V60, V90, V60 cross country (from 2015), XC60 and XC90.

Nederman

Exhaust Nozzles

| | [accessory] | [partno] |
|---|--|-----------|
| | Quick safety coupler incl. rubber sleeves and hose clips, Ø100 | 20374541* |
| | Quick safety coupler incl. rubber sleeves and hose clips, Ø150 | 20374543* |
| | Quick coupler, male, Ø100 incl. rubber sleeves and hose clip | 20375049* |
| | Quick coupler, male, Ø150 incl. rubber sleeves and hose clip | 20376017 |
| 8 | Connection kit 4" for quick coupler | 20375048 |
| | Adaptor for 3" hose | 20373128 |
| | Adapter for double exhaust pipes, L=1,0 m, ø 100 mm | 20815061 |
| | Telescopic lifting pole 3m for 20808861, 20816661, 20816761 | 20374287 |
| Ô | Quick coupler 100mm (2 pcs) | 20374641 |

*Use the key ring on the one end of the coupling to more easily connect and reconnect the two hose ends or to disconnect the two hose ends.