

Exhaust Nozzles

High temperature resistant rubber and metal exhaust hoses



Nederman offers an extensive range of robust rubber and metal vehicle exhaust extraction nozzles to accommodate various types of vehicles. Adjustable test funnels with special design to handle large volumes of hot exhaust. Also available with adjustable floor stand to accommodate most exhaust pipe positions and designs.

- Easy manual connection and disconnection of the exhaust nozzles
- Well proven nozzles with a soft capturing hood that protects employees and vehicles
- The nozzles are resistant to very high exhaust temperatures up to 400°C (752°F) in normal use

Product name	Exhaust Nozzles
Installation	[Indoor]



Exhaust Nozzles

[image]	Description	Max exhaust pipe, diameter. Dual (in)	Vehicle type	Max exhaust pipe, single (in)	Hose connection Diameter (in)	[model]
	Rubber nozzle with lid and metal hose	12		6	4	20803161
	Rubber nozzle with lid and metal hose			6	5	20803261
	Rubber nozzle with lid and metal hose			6	6	20803361
	Rubber nozzle, triangular, Spring-loaded lid, wire guard and opening for CO probe	4 x 3		3	3	20803461
	Rubber nozzle, triangular, Spring-loaded lid, wire guard and opening for CO probe	4 x 3		3	4	20803561
	Rubber nozzle, triangular, Spring-loaded lid, wire guard and opening for CO probe	4 x 3		3	5	20803661
	Rubber nozzle, triangular with lid	4 x 3		3	3	20804061
	Rubber nozzle, triangular with lid	4 x 3		3	4	20804161
	Rubber nozzle, triangular with lid	4 x 3		3	5	20804261
	Rubber nozzle, oval, opening for CO probe. Hose connection angled 60 deg.	4 x 3		3	3	20805461
	Rubber nozzle, oval, opening for CO probe. Hose connection angled 60 deg.	4 x 3		3	4	20805561
	Rubber nozzle, round, with lid	n.a.		6	6	20805961
	Rubber nozzle, oval for variable pipe thickness	6 x 3		3	4	20808361
	Rubber nozzle, oval, opening for CO probe. Hose connection angled 60 deg.	8 x 4		4	5	20805661
	Rubber nozzle, oval, opening for CO probe. Hose connection angled 60 deg.	8 x 4		4	6	20805761



Exhaust Nozzles

[image]	Description	Max exhaust pipe, diameter. Dual (in)	Vehicle type	Max exhaust pipe, single (in)	Hose connection Diameter (in)	[model]
	Rubber nozzle, oval, opening for CO probe. Hose connection angled 60 deg.	n.a.		6	5	20805861
	Rubber nozzle, oval, automatic wire release	150 x 75		6	4	20806161
	Rubber nozzle, round, swivel and lengthwise compressible	9.5 x 9		7	6	20806961
	Rubber nozzle, round, swivel and lengthwise compressible	9.5 x 9		9	8	20807061
	Rubber nozzle, oval, Spring-loaded lid, wire guard and opening for CO probe. Without locking clamp	6 x 4,5		4	4	20802561
	Rubber nozzle, with safety disconnection, automatic release	n.a.		6	6	20807861
	Aluminium nozzle with wire guard	n.a.		5	6	20804761
	Aluminium nozzle with wire guard	n.a.		7	8	20804961
	Rubber nozzle . Slips on to the exhaust pipe without locking device			4	3/4	20815261
	Rubber nozzle . Slips on to the exhaust pipe without locking device				100	20817261
	Beak nozzle			100	4	20866461
	Beak nozzle			3	3	20866561
	Beak nozzle	6 x 3		5	6	20866661
	Beak nozzle	6 x 3		5	5	20866761
	Beak nozzle	6 x 3		5	4	20866861

Exhaust Nozzles

[image]	Description	Max exhaust pipe, diameter. Dual (in)	Vehicle type	Max exhaust pipe, single (in)	Hose connection Diameter (in)	[model]
	Beak nozzle	6 x 3		5	3	20866961
	Nozzle for built-in and covered exhaust pipes. Internal grip.	9.5 x (3-4)		2-3	4	20867261
	Nozzle for built-in and covered exhaust pipes. Internal grip. Includes quick coupling for the exhaust hose.	9.5 x (3-4)		2-3	4	20867661
	Nozzle for built-in and covered exhaust pipes. Internal grip and extension hood.	9.5 x (3-4)		65	4	20867861
	For Cars with twin pipes.	Oval 10 x 3			4	20867761
	Rubber funnel on floor stand. Height 0 - 600 mm (23").				4	20868361
	Funnel on floor stand with wheels. Height 0 - 600 mm (23").				150	20816861
	Nozzle on floor stand. Height 130 - 440 mm				200	20807261
	Large aluminum generic funnel. Suitable for EURO 6 trucks. With high temperature resistant kevlar based hose.				150	20817061
	Aluminum funnel incl. With high temperature resistant kevlar based hose.				150	20817161
	Flexible stand for funnels 20817061, 20817161 and nozzle 20817261.				3	20816961
	Galvanised steel nozzle for stack pipes, length 2600 mm	n.a.		10	5	20801961
	Rubber nozzle for vertical stack	n.a.		10	5/6/7	20808861
	Nozzle for exhaust Pipe internal size 140 x 58mm / 5.5" x 2.28"				4	20869761*
	Nozzle for exhaust Pipe internal size 175 x 60mm / 6.8" x 2.36"				4	20869861**

Exhaust Nozzles

[image]	Description	Max exhaust pipe, diameter. Dual (in)	Vehicle type	Max exhaust pipe, single (in)	Hose connection Diameter (in)	[model]
	Nozzle for exhaust Pipe internal size 126 x 80mm / 4.96" x 3.15"				4	20869961***
	Nozzle for exhaust Pipe internal size 175 x 85mm / 6.8" x 3.35"				4	20870061****
						89299170
						89298076
						89298102
						89298103
						89298104
						88000315
						88000653

*For Mercedes C, Mercedes CLA, Mercedes E GLE and Ford Mondeo 2015.

**For Audi A6 2015 and Citroën DS

***For Volvo XC60, V60 and S60 (Before 2015), Mercedes R, GLK and GLA 2015, Mercedes E (Before 2013) and Porsche Cayenne.

****For Volvo S60, S90, S60 cross country (From 2015), V40, V60, V90, V60 cross country (from 2015), XC60 and XC90.

Exhaust Nozzles

	[accessory]	[partno]
	Quick safety coupler incl. rubber sleeves and hose clips, Ø100	20374541*
	Quick safety coupler incl. rubber sleeves and hose clips, Ø150	20374543*
	Quick coupler, male, Ø100 incl. rubber sleeves and hose clip	20375049*
	Quick coupler, male, Ø150 incl. rubber sleeves and hose clip	20376017
	Connection kit 4" for quick coupler	20375048
	Adaptor for 3" hose	20373128
	Adapter for double exhaust pipes, L=1,0 m, ø 100 mm	20815061
	Telescopic lifting pole 3m for 20808861, 20816661, 20816761	20374287**
	Quick coupler 100mm (4 in) - 2 pcs	20374641

*Use the key ring on the one end of the coupling to more easily connect and reconnect the two hose ends or to disconnect the two hose ends.

**For use with 20808861 and stainless steel nozzles