

High temperature resistant rubber and metal exhaust hoses



Nederman offer an extensive range of robust rubber and metal vehicle exhaust extraction nozzles to accommodate various types of vehicles and systems including European standard EURO 6 engines. Adjustable test funnels with special design to handle large volumes of hot exhaust from vehicles in inspection centres for example. Also available with floor stand and for vertical exhaust pipes. The adjustable floor stand accommodates most exhaust pipe positions and designs.

- Easy manual connection and disconnection of the exhaust nozzles
- Well proven nozzles with a soft capturing hood that protects employees and vehicles
- The nozzles are resistant to high exhaust temperature up to 150°C (300°F) for rubber nozzles and up to 400°C (750°F) for metal nozzles, in normal use

Product name	Exhaust Nozzles
Installation	[Indoor]

 ϵ



[image]	Description	Max exhaust pipe, diameter. Dual (mm)	Vehicle type	Max exhaus pipe, single (mm)	Hose connection Diameter (mm)	[model]
	Rubber nozzle with lid and metal hose	n.a.		150	100	20803161
	Rubber nozzle with lid and metal hose	n.a.		150	125	20803261
	Rubber nozzle with lid and metal hose	n.a.		150	150	20803361
	Rubber nozzle, triangular, Spring-loaded lid, wire guard and opening for CO probe	100 x 75		75	75	20803461
	Rubber nozzle, triangular, Spring-loaded lid, wire guard and opening for CO probe	100 x 75		75	100	20803561
	Rubber nozzle, triangular, Spring-loaded lid, wire guard and opening for CO probe	100 x 75		75	125	20803661
4	Rubber nozzle, triangular with lid	100 x 75		75	75	20804061
4	Rubber nozzle, triangular with lid	100 x 75		75	100	20804161
4	Rubber nozzle, triangular with lid	100 x 75		75	125	20804261
	Exhaust Nozzle Rubber Ø100 (4") Manual Triangular. With metal hose. With lid	100 x 75		75	100	20322139
	Exhaust Nozzle Rubber Manual With metal hose With lid	n.a.		150	150	20322140
-	Rubber nozzle, oval, opening for CO probe. Hose connection angled 60 deg.	150 x 75		75	75	20805461
-	Rubber nozzle, oval, opening for CO probe. Hose connection angled 60 deg.	150 x 75		75	100	20805561
	Rubber nozzle, round, with wireguard	n.a.		150	150	20805961
-	Rubber nozzle, oval for variable pipe thickness	150 x 75		75	100	20808361



[image]	Description	Max exhaust pipe, diameter. Dual (mm)	Vehicle type	Max exhaus pipe, single (mm)	Hose connection Diameter (mm)	[model]
	Rubber nozzle, oval, opening for CO probe. Hose connection angled 60 deg.	200 x 100		100	125	20805661
	Rubber nozzle, oval, opening for CO probe. Hose connection angled 60 deg.	200 x 100		100	150	20805761
	Rubber nozzle, round, with wireguard CO probe. Hose connection angled 60 deg.	n.a.		150	125	20805861
	Rubber nozzle, oval, automatic wire release	150 x 75		75	100	20806161
	Rubber nozzle,round, automatic wire release	n.a.		150	125	20806461
	Rubber nozzle, round, automatic wire release	n.a.		150	150	20806561
	Rubber nozzle, round, swivel and lengthwise compressible	240 x 230		180	150	20806961
	Rubber nozzle, round, swivel and lengthwise compressible	240 x 230		230	200	20807061
	Rubber nozzle, oval, Spring-loaded lid, wire guard and opening for CO probe. Without locking clamp	150 x 110		110	100	20802561
	Rubber nozzle, with safety disconnection, automatic release	n.a.		150	150	20807861
	Aluminium nozzle with wire guard	n.a.		125	150	20804761
	Aluminium nozzle with wire guard	n.a.		170	200	20804961
	Rubber nozzle . Slips on to the exhaust pipe without locking device			100	75/100	20815261
	Rubber nozzle . Slips on to the exhaust pipe without locking device				100	20817261
	Beak nozzle			100	100	20866461



[image]	Description	Max exhaust pipe, diameter. Dual (mm)	Vehicle type	Max exhaus pipe, single (mm)	Hose connection Diameter (mm)	[model]
	Beak nozzle			75	75	20866561
	Beak nozzle	150 x 80		125	150	20866661
	Beak nozzle	150 x 80		125	125	20866761
	Beak nozzle	150 x 80		125	100	20866861
	Beak nozzle	150 x 80		125	75	20866961
	Nozzle for built-in and covered exhaust pipes. Internal grip.	240 x (50-65)		65	100	20867261
	Nozzle for built-in and covered exhaust pipes. Internal grip. Includes quick coupling for the exhaust hose.	240 x (50-65)		65	100	20867661
	Nozzle for built-in and covered exhaust pipes. Internal grip and extension hood.	270 x (50-65)		65	100	20867861
	For Cars with twin pipes.	250 x 80			100	20867761
	Rubber funnel on floor stand. Height 0 - 600 mm, rotatable				100	20868361
Quit.	Funnel on floor stand with wheels. Height 0 - 600 mm, rotatable				150	20816861
•	Nozzle on floor stand. Height 130 - 440 mm				200	20807261
av	Large aluminum generic funnel. Suitable for EURO 6 trucks. With high temperature resistant kevlar based hose.				150	20817061
05	Aluminum funnel incl. With high temperature resistant kevlar based hose.				150	20817161
000	Flexible stand for funnels 20817061 , 20817161 and nozzle 20817261.				75	20816961



[image]	Description	Max exhaust pipe, diameter. Dual (mm)	Vehicle type	Max exhaus pipe, single (mm)	Hose connection Diameter (mm)	[model]
1	Galvanised steel nozzle for stack pipes, length 2600 mm	n.a.		250	140	20801961
	Rubber nozzle for vertical stack	n.a.		250	125/150/200	20808861
1	Galvanized nozzle for vertical stacks	n.a.		250	150	20816661
A	Galvanized nozzle for vertical stacks	n.a.		250	200	20816761
•	Nozzle for exhaust Pipe internal size 140 x 58mm				100	20869761*
	Nozzle for exhaust Pipe internal size 175 x 60mm				100	20869861**
0.	Nozzle for exhaust Pipe internal size 126 x 80mm				100	20869961***
0:	Nozzle for exhaust Pipe internal size 175 x 85mm				100	20870061****

^{*}For Mercedes C, Mercedes CLA, Mercedes E GLE and Ford Mondeo 2015.

^{**}For Volvo XC60, V60 and S60 (Before 2015), Mercedes R, GLK and GLA 2015, Mercedes E (Before 2013) and Porsche Cayenne.
***For Volvo S60, S90, S60 cross country (From 2015), V40, V60, V90, V60 cross country (from 2015), XC60 and XC90.



	[accessory]	[partno]
	Quick safety coupler incl. rubber sleeves and hose clips, Ø100	20374541*
	Quick safety coupler incl. rubber sleeves and hose clips,, Ø150	20374543*
	Quick coupler, male, Ø100 incl. rubber sleeves and hose clip	20375049*
	Quick coupler, male, Ø150 incl. rubber sleeves and hose clip	20376017
8	Connection kit 4" for quick coupler	20375048
N. Company	Adaptor for 3" hose	20373128
	Adapter for double exhaust pipes, L=1,0 m, ø 100 mm	20815061
	Telescopic lifting pole 3m for 20808861, 20816661, 20816761	20374287
0	Quick coupler 100mm (2 pcs)	20374641

^{*}Use the key ring on the one end of the coupling to more easily connect and reconnect the two hose ends or to disconnect the two hose ends.