

## Hose Reel 883

Retractable hose reel suitable for vehicle repair shops, garages and maintenance workshops.



A fully plate encased and robust, medium sized retractable hose reel. A highly suitable hose reel for applications in vehicle repair and maintenance workshops. The retractable hose reel is supplied with loose quick hitch for easy installation.













The hose reel 883 is retractable and has an optimized spring force, ensuring that the hose retracts smoothly and evenly onto the drum. The high quality spring is pre-tensioned at the factory to suit a wide range of applications, and is well protected inside the drum cavity. The self retracting hose reel 883 is very easy to mount, either on walls, ceilings or floors.

- Spring tension easily adjustable from the outside.
- Fast and easy to service.
- Simple hose replacement without dismantling the reel.









Product name	Hose Reel 883
Material	Sheet metal casing
Material recycling (%)	100
Media	Compressed air, Water, Water high pressure, Oil, Grease
Connection hose length (m)	1
Weight (kg)	15
Corrosion resistance	Standard
Electric/Spring driven	Spring



## Hose Reel 883

Image	Type of hose <sup>1</sup>	Media	Delivered with hose	Colour	Distribution hose length (m)	Diameter, connection hose (mm)	Distribution hose diameter (mm)	Max working pressure (Mpa)	Max hose length	Model
		Compressed air ,Water	No	Black				1,5	15	30800783*
		Compressed air ,Water	No	Black			12.5	1,5	10	30800983**
	B	Compressed air ,Water	Yes	Black	10	12.5	12.5	1,5		30801083
		Compressed air ,Water ,Oil	No	Black			12.5	7,5	10	30801183**
		Grease	No	Black			6	35	15	30801383***
		Water high pressure	No	Black			10	25	13	30802183*
	G	Water high pressure	Yes	Black	13	10	10	25		30802283
	G	Water high pressure	Yes	White	13	10	10	25		30803883
		Water high pressure	No	White			10	25	13	30803783*
	I	Oil	Yes	Black	10	12.5	12.5	7,5		30801283
		Oil	No	White			12.5	7,5	10	30806183
	I	Compressed air ,Water ,Oil	Yes	White	10	12.5	12.5	7,5		30806283
	J	Grease	Yes	Black	15	6	6	35		30801883
	B	Compressed air ,Water	Yes	White	15	12.5	10	1,5		30807283
	B	Compressed air ,Water	Yes	White	10	12.5	12.5	1,5		30851683

## Hose Reel 883

Image	Type of hose <sup>1</sup>	Media	Delivered with hose	Colour	Distribution hose length (m)	Diameter, connection hose (mm)	Distribution hose diameter (mm)	Max working pressure (Mpa)	Max hose length	Model
	G	Grease	Yes	White	15	6	6	35		30825283
	G	Grease	Yes	White	10	10	10	25		30825483
	I	Compressed air ,Water ,Oil	Yes	Grey	10	12.5	12.5	7,5		30803283
	J	Grease	Yes	Grey	10	10	10	35		30806083
	B	Compressed air ,Water	Yes	Grey	15		10	1,5		30815483**
	Q		Yes	Grey	15	10	10	1,5		30809783***
	Q		Yes	Black	15	10	10	1,5		30809683***
	B	Compressed air ,Water	Yes	Black	15	12,5	10	1,5		30800883

\*For 10 mm hose

\*\*For 12,5 mm hose



\*\*\*For 6 mm hose

\*\*\*\*Hose couplings are 12mm (1/2")

<sup>1</sup> See table below

Hose type	Specification	Temperature range, °C	Hose fittings in free hose end, distribution hose	Hose fitting on free hose end, inlet hose	Hose connection on reel, distribution hose	Hose connection on reel, inlet hose
B	Cover in NBR/PVC and inner tube in NBR. Synthetic textile braid	-30 - 100			Hose nipple + clip	Hose nipple 1/2 + clip
G	Cover and inner tube in synthetic rubber. Single steel braid	-40 - 155		Female 60° cone, chrome plated	Male 60° cone	Male 60° cone
I	Cover and inner tube in SBR based rubber. Single steel braid	-40 - 100		Female 60° cone, chrome plated	Male 60° cone	Male 60° cone
J	Cover and inner tube in synthetic, oil resistant rubber. Double steel braid	-40 - 100		Female 60° cone, chrome plated	Male 60° cone	Male 60° cone
Q		-40 to +70				

## Hose Reel 883

	Accessory	Part No
	Roller guide.	30341550
	Pivoting bracket.	30372407
	Water gun in chromium plated brass	30400110
	Water gun in stainless steel 316	30400210
	Water gun EX	30400211
	Water gun in stainless steel 316	30400310
	Air gun, standard.	30410110
	Swivelling coupling 3/8(m)-3/8(m)HP	30431310
	Swiv. coupling 3/8(m)-3/8(m) HP SS	30431410
	Swivl. coupl.1/2(m)-3/8(f) brass	30431510
	Swivl.coupl.1/2(m)-1/2(f) brass	30431610
	Swivel coupling 1/2(m)- 3/4 (f) bra	30431710
	Swivl. coupl. 1/2(m)-3/8(f) SS	30431810
	Swivl coupl. 1/2(m)-1/2(f) SS	30431910
	Swivl.coupl.1/2(m)-3/4(f) SS	30432010
	Inlet kit for hose reel 1/2" with ball valve	30511550
	Inlet kit for hose reel 3/8"	30511650
	Inlet kit for hose reel 1/2"	30511750

## Hose Reel 883

