

Medium sized open hose reel.



Thanks to the open design, the reels are very easy to service, maintain and keep clean. Can be installed on wall or on the ceiling.

- Outlet position can be adjusted through 120° for optimum pullout and pull-in angle.
- Spring power can easily be adjusted from the outside.
- Ratchet easily disengaged when required.

Product name	Hose Reel 888
Connection hose length (m)	1
Corrosion resistance	Standard
Electric/Spring driven	Spring

CE



[image]	Type of hose	Media	Delivered with hose	Colour	Distribution hose length (m)	Diameter, connection hose (mm)	Distribution hose diameter (mm)	Max working pressure (Mpa)	Weight (kg)	Max hose length	[model]
	В	Compressed air ,Water		Black drum / Blue arm	10	12.5	12.5	1,5	16		30800888
	E	Water		Black drum / Blue arm	10	12.5	12.5	2	16		30801088
	G	Water high pressure		Black drum / Blue arm	15	10	10	25	16		30801888
	J			Black drum / White arm	15	10	10	35	18		30804288
	I	Oil		Black drum / White arm	10	12.5	12.5	7,5	16		30804688
	J			Black drum / White arm	15	6	6	35	16		30804888
	J			Black drum / White arm	10	10	10	35	14		30805088
	В	Compressed air ,Water		Black drum / White arm	15	12.5	10	1,5	11		30851088
	I	Oil		Black drum / Blue arm	10	12.5	12.5	7,5	16		30801688
	J			Black drum / Blue arm	15	6	6	35	16		30802688
		Compressed air ,Water		Black drum / Blue arm			10	1,5	11	15	30800388
		Compressed air ,Water		Black drum / Blue arm			12.5	1,5	11	10	30800788
	G	Water high pressure		Black drum / Blue arm			10	25	11	15	30801788
	I	Oil		Black drum / Blue arm			12.5	7,5	11	10	30801588
	J			Black drum / Blue arm			6	35	11	15	30802588

This content is protected under copyright law, furnished for informational use only, and subject to change without notice. © Nederman Holding AB www.nederman.com 2



[image]	Type of hose	Media	Delivered with hose	Colour	Distribution hose length (m)	Diameter, connection hose (mm)	Distribution hose diameter (mm)	Max working pressure (Mpa)	Weight (kg)	Max hose length	[model]
	В	Compressed air ,Water		Black drum / Blue arm	15	12.5	10	1,5	16		30800688

¹ See table below

Hose type	Specification	Temperature range, °C	Hose fittings in free hose end, distribution hose	Hose fitting on free hose end, inlet hose	Hose connection on reel, distribution hose	Hose connection on reel, inlet hose
В		-30 - 100				
E		-30 - 100				
G		-40 - 155				
J		-40 - 100				
I		-40 - 100				



	[accessory]	[partno]
Ø	Roller guide.	30341550
	Pivoting bracket.	30372407
1	Water gun in chromium plated brass	30400110
T	Water gun in stainless steel	30400210
	Watergun EX	30400211
	High temperature water gun	30400310
	Air gun, standard.	30410110
	Swivelling coupling 3/8(m)-3/8(m)HP	30431310
	Swiv. coupling 3/8(m)-3/8(m) HP SS	30431410
	Swivl. coupl.1/2(m)-3/8(f) brass	30431510
	Swivl.coupl.1/2(m)-1/2(f) brass	30431610
	Swivel coupling 1/2(m)- 3/4 (f) bra	30431710
	Swivl. coupl. 1/2(m)-3/8(f) SS	30431810
	Swivl coupl. 1/2(m)-1/2(f) SS	30431910
	Swivl.coupl.1/2(m)-3/4(f) SS	30432010
20	nlet kit for hose reel 1/2" with ball valve	30511550
S.S.	nlet kit for hose reel 3/8" with ball valve 3/8", 3/8"-3/8" adapter and 1/4" - 3/8" adapter.	30511650
180	Inlet kit for hose reel 1/2" with ball valve 1/2", 1/2" adapter, 1/2"-1/2" nipple and hose clamp	30511750



