

Medium sized open hose reel.



Fitted with slightly larger drums and therefore are able to take longer hoses than Series 888.Thanks to the open design, the reels are very easy to service, maintain and keep clean. Can be installed on wall or on the ceiling.

- Outlet position can be adjusted through 120° for optimum pullout and pull-in angle.
- Spring power can easily be adjusted from the outside.
- Ratchet easily disengaged when required.

Product name	Hose Reel 889
Media	Compressed air, Water, Water high pressure, Oil, [adblue]
Connection hose length (m)	1
Note	AdBlue
Corrosion resistance	Standard
Electric/Spring driven	Spring

CE



Image	Type of hose	Media	Delivered with hose	Colour	Distribution hose length (m)	Diameter, connection hose (mm)	Distribution hose diameter (mm)	Max working pressure (Mpa)	Weight (kg)	Max hose length	Model
		Compressed air ,Water	No	Black drum / Blue arm			10	1,5	11	20	30800589
	В	Compressed air ,Water	Yes	Black drum / Blue arm	20	12.5	10	1,5	16		30800689
		Compressed air ,Water	No	Black drum / Blue arm			12.5	1,5	11	15	30800789
	В	Compressed air ,Water	Yes	Black drum / Blue arm	15	12.5	12.5	1,5	16		30800889
	E	Water	Yes	Black drum / Blue arm	13+2	12.5	12.5	2	16		30801089
		Oil	No	Black drum / Blue arm			12.5	7,5	11	15	30801589
	I	Oil	Yes	Black drum / Blue arm	15	12.5	12.5	7,5	16		30801689
		Water high pressure	No	Black drum / Blue arm			10	25	11	18	30801789
	G	Water high pressure	Yes	Black drum / Blue arm	18	10	10	25	16		30801889
	I	Oil	Yes	Black drum / Blue arm	20	12.5	12.5	7,5	16		30802489
	М		Yes	Black drum / Blue arm	15		15	1	16		30803089*
	I	Oil	Yes	Black drum / White arm			12.5	7,5	16		30804489
	М	Compressed air ,Water	Yes	Black drum / White arm	15	12.5	12.5	1,5	16		30804889
	М	Compressed air ,Water	Yes	Black drum / White arm	20	12.5	10	1,5	16		30851089

*AdBlue

¹ See table below

Nederman

Hose Reel 889

Hose type	Specification	Temperature range, °C	Hose fittings in free hose end, distribution hose	Hose fitting on free hose end, inlet hose	Hose connection on reel, distribution hose	Hose connection on reel, inlet hose
В	Cover in NBR/PVC and inner tube in NBR. Syntethic textile braid	-30 - 100			Hose nipple + clip	Hose nipple 1/2 + clip
E	Cover in NBR/PVC and inner tube in food grade quality NBR. Syntethic textile braid	-30 - 100		Female 60° cone, chrome plated	Male 60° cone	Male 60° cone
I	Cover and inner tube in SBR based rubber. Single steel braid	-40 - 100		Female 60° cone, chrome plated	Male 60° cone	Male 60° cone
G	Cover and inner tube in synthetic rubber. Single steel braid	-40 - 155		Female 60° cone, chrome plated	Male 60° cone	Male 60° cone
М	Cover in CR and inner tube in NBR. Synthetic textile braid. Electrically conductive	-30 - 80		Female 60° cone, stainless steel	Male 60° cone	Male 60° cone



	Accessory	Part No
Ø	Roller guide.	30341550
	Pivoting bracket.	30372407
1	Water gun in chromium plated brass	30400110
<u>7</u>	Water gun in stainless steel 316	30400210
	Water gun EX	30400211
	Water gun in stainless steel 316	30400310
	Air gun, standard.	30410110
	Swivelling coupling 3/8(m)-3/8(m)HP	30431310
	Swiv. coupling 3/8(m)-3/8(m) HP SS	30431410
	Swivl. coupl.1/2(m)-3/8(f) brass	30431510
	Swivl.coupl.1/2(m)-1/2(f) brass	30431610
	Swivel coupling 1/2(m)- 3/4 (f) bra	30431710
	Swivl. coupl. 1/2(m)-3/8(f) SS	30431810
	Swivl coupl. 1/2(m)-1/2(f) SS	30431910
	Swivl.coupl.1/2(m)-3/4(f) SS	30432010
20	Inlet kit for hose reel 1/2" with ball valve	30511550
in the second	Inlet kit for hose reel 3/8"	30511650
120	Inlet kit for hose reel 1/2"	30511750



