

Medium sized open stainless steel hose reel.



Fitted with slightly larger drums and are therefore able to take a little longer hose than Series 888. These reels are ideal in environments with high humidity, where hygiene is of the utmost importance or where there is a risk of chemical attack. Thanks to the open design, the reels are very easy to service, maintain and keep clean. Can be installed on wall or on the ceiling.

- All components in stainless steel and chemically resistant composite.
- Open design for ease of cleaning.
- Outlet position can be adjusted through 120° for optimum pull-out and pull-in angle.

Product name	Hose Reel 889 Stainless
Connection hose length (m)	1
Colour	Stainless
Corrosion resistance	Stainless steel
Electric/Spring driven	Spring

 $\epsilon$ 



[image]	Type of hose <sup>1</sup>	Media	Delivered with hose	Distribution hose length (m)	Diameter, connection hose (mm)	Distribution hose diameter (mm)	Max working pressure (Mpa)	Weight (kg)	Max hose length	[model]
		Water				12.5	2	14	15	30803589
		Water		15	12.5	12.5	2	18		30803689
		Water high pressure				10	25	11	20	30803789
		Water high pressure		20	10	10	25	18		30803889

<sup>&</sup>lt;sup>1</sup> See table below

Hose type	Specification	Temperature range, °C	Hose fittings in free hose end, distribution hose	Hose fitting on free hose end, inlet hose	Hose connection on reel, distribution hose	Hose connection on reel, inlet hose
Е		-30 - 100				
G		-40 - 155				



	[accessory]	[partno]
	Roller guide.	30341550
	Pivoting bracket.	30372407
6	Pivoting bracket ss.	30372408
<b>*</b>	Water gun in chromium plated brass	30400110
	Water gun in stainless steel	30400210
	Watergun EX	30400211
	High temperature water gun	30400310
	Air gun, standard.	30410110
	Swivelling coupling 3/8(m)-3/8(m)HP	30431310
	Swiv. coupling 3/8(m)-3/8(m) HP SS	30431410
	Swivl. coupl.1/2(m)-3/8(f) brass	30431510
	Swivl.coupl.1/2(m)-1/2(f) brass	30431610
	Swivel coupling 1/2(m)- 3/4 (f) bra	30431710
	Swivl. coupl. 1/2(m)-3/8(f) SS	30431810
	Swivl coupl. 1/2(m)-1/2(f) SS	30431910
	Swivl.coupl.1/2(m)-3/4(f) SS	30432010





