

Medium sized open stainless steel hose reel.



Medium-sized open reel in stainless steel which is ideal in environments with high humidity, where hygiene is of the utmost importance and there is a risk of chemical attack. Thanks to the open design, the reel is very easy to service, maintain and keep clean. Can be installed on wall or on the ceiling.

- All components in stainless steel and chemical-proof composite.
- Outlet position can be adjusted for optimum pull-out and pull-in angle.
- Adjustable outlet minimizes friction
- Available with low pressure water food grade hose as well as high pressure water hose

| Product name | Hose Reel 893 Stainless |
|----------------------------|--------------------------------------|
| Connection hose length (m) | 1 |
| Colour | Stainless |
| Note | Hoses with stainless steel fittings. |
| Corrosion resistance | Stainless steel |
| Electric/Spring driven | Spring |



| Type of hose ¹ | Media | Delivered with hose | Distribution hose length (m) | Diameter, connection hose (mm) | Distribution hose diameter (mm) | Max working pressure (Mpa) | Weight (kg) | Max hose length | Model |
|---------------------------|---------------------|------------------------|---------------------------------|--------------------------------------|---------------------------------------|-------------------------------|-------------|-----------------|-----------|
| | Water | No | | 12,5 | 12.5 | 7,5 | 16 | 10 | 30803193 |
| E | Water | Yes | 10 | 12.5 | 12.5 | 2 | 16 | | 30803293 |
| | Water high pressure | No | | 10 | 10 | 25 | 16 | 15 | 30803393 |
| G | Water high pressure | Yes | 15 | 10 | 10 | 25 | 16 | | 30803493 |
| E | Water | Yes | 10 | 12.5 | 12.5 | 2 | 14,5 | | 30804493* |

*Hoses with stainless steel fittings.

¹ See table below

| Hose type | Specification | Temperature range, °C | Hose fittings in free hose end, distribution hose | Hose fitting on free hose end, inlet hose | Hose connection on reel, distribution hose | Hose connection on reel, inlet hose |
|-----------|---|-----------------------|---|---|--|-------------------------------------|
| E | Cover in NBR/PVC and inner tube in food grade quality NBR. Syntethic textile braid | -30 - 100 | | Female 60° cone, chrome plated | Male 60° cone | Male 60° cone |
| G | Cover and inner tube in synthetic rubber. Single steel braid | -40 - 155 | | Female 60° cone, chrome plated | Male 60° cone | Male 60° cone |



| | Part No | | | |
|----------|-------------------------------------|----------|--|--|
| | Roller guide. | | | |
| | Pivoting bracket. | 30372407 | | |
| Ś | Pivoting bracket ss. | 30372408 | | |
| 1 | Water gun in chromium plated brass | 30400110 | | |
| <u>J</u> | Water gun in stainless steel 316 | 30400210 | | |
| | Water gun EX | 30400211 | | |
| | Water gun in stainless steel 316 | 30400310 | | |
| | Air gun, standard. | 30410110 | | |
| | Swivelling coupling 3/8(m)-3/8(m)HP | 30431310 | | |
| | Swiv. coupling 3/8(m)-3/8(m) HP SS | 30431410 | | |
| | Swivl. coupl.1/2(m)-3/8(f) brass | 30431510 | | |
| | Swivl.coupl.1/2(m)-1/2(f) brass | 30431610 | | |
| | Swivel coupling 1/2(m)- 3/4 (f) bra | 30431710 | | |
| | Swivl. coupl. 1/2(m)-3/8(f) SS | 30431810 | | |
| | Swivl coupl. 1/2(m)-1/2(f) SS | 30431910 | | |
| | Swivl.coupl.1/2(m)-3/4(f) SS | | | |



