

Medium sized open stainless steel hose reel.



Medium-sized open reel in stainless steel which is ideal in environments with high humidity, where hygiene is of the utmost importance and there is a risk of chemical attack. Thanks to the open design, the reel is very easy to service, maintain and keep clean. Can be installed on wall or on the ceiling.

- All components in stainless steel and chemical-proof composite.
- Outlet position can be adjusted for optimum pull-out and pull-in angle.
- Adjustable outlet minimizes friction
- Available with low pressure water food grade hose as well as high pressure water hose

Product name	Hose Reel 893 Stainless
Connection hose length (m)	1
Colour	Stainless
Note	Hoses with stainless steel fittings.
Corrosion resistance	Stainless steel
Electric/Spring driven	Spring



Type of hose ¹	Media	Delivered with hose	Distribution hose length (m)	Diameter, connection hose (mm)	Distribution hose diameter (mm)	Max working pressure (Mpa)	Weight (kg)	Max hose length	[model]
	Water			12,5	12.5	7,5	16	10	30803193
E	Water		10	12.5	12.5	2	16		30803293
	Water high pressure			10	10	25	16	15	30803393
G	Water high pressure		15	10	10	25	16		30803493
E	Water		10	12.5	12.5	2	14,5		30804493*

*Hoses with stainless steel fittings.

¹ See table below

Hose type	Specification	Temperature range, °C	Hose fittings in free hose end, distribution hose	Hose fitting on free hose end, inlet hose	Hose connection on reel, distribution hose	Hose connection on reel, inlet hose
E		-30 - 100				
G		-40 - 155				



	[partno]			
Ø	Roller guide.	30341550		
	Pivoting bracket.	30372407		
(c)	Pivoting bracket ss.	30372408		
1	Water gun in chromium plated brass	30400110		
T	Water gun in stainless steel	30400210		
	Watergun EX	30400211		
	High temperature water gun	30400310		
	Air gun, standard.	30410110		
	Swivelling coupling 3/8(m)-3/8(m)HP	30431310		
	Swiv. coupling 3/8(m)-3/8(m) HP SS	30431410		
	Swivl. coupl.1/2(m)-3/8(f) brass	30431510		
	Swivl.coupl.1/2(m)-1/2(f) brass	30431610		
	Swivel coupling 1/2(m)- 3/4 (f) bra	30431710		
	Swivl. coupl. 1/2(m)-3/8(f) SS	30431810		
	Swivl coupl. 1/2(m)-1/2(f) SS	30431910		
	Swivl.coupl.1/2(m)-3/4(f) SS			



