

Stainless steel hose reel when corrosive resistance is required ideal for food processing industries.



This stainless steel hose reel, made entirely of stainless steel, is designed specifically for the food processing industry. It is very easy to clean thanks to rounded edges and features an easy to dismantle hose outlet, an externally mounted swivel, and a minimum number of material joints.

- Unique design makes easy cleaning
- Up to 25 m (82 ft.) hose capacity
- Meets international hygienic requirement

Product name	Hose Reel 886 Stainless
Connection hose length (m)	-
Delivered with hose	No
Colour	Stainless
Corrosion resistance	Stainless steel
Electric/Spring driven	Spring





lmage	Description	Type of hose <sup>1</sup>	Media	Distribution hose length (m)	Diameter, connection hose (mm)	Distribution hose diameter (mm)	Max working pressure (Mpa)	Weight (kg)	Max hose length	Model
			Water high pressure	25		10	150°C max 10MPa 50°C max 25MPa	28	25	30801386
			Water	25		12.5	10	28	25	30800386
			Water	18		19	2	28	18	30800186
			Water	10		25	2	28	10	30802186
						19	0,6 (Steam, 160°C) 2,0 (Water)	28	18	30805286
						25	0,6 (Steam, 160°C) 2,0 (Water)	28	10	30805086
	Connection Hose (1m)	I	Water		12,5		2	1		30344854*
	Connection Hose (1m)	G	Water high pressure		10		25			30344852**
	Connection Hose (1m)	Н	Water high pressure		10		25			30373669***
	Connection Hose (1m)	Е	Water ,Food		12,5		2			30373670**
	Connection Hose (1m)	Е	Water ,Food		19		2			30373674**
	Connection Hose (1m)	Е	Water ,Food		25		2			30373664**
	Connection Hose (1m)	F	Water ,Food		19		2			30373675***
	Connection Hose (1m)	F	Water ,Food		12,5		2			30373671***
	Connection Hose (1m)	F	Water ,Food		25		2			30373666***



Image	Description	Type of hose <sup>1</sup>	Media	Distribution hose length (m)	Diameter, connection hose (mm)	Distribution hose diameter (mm)	Max working pressure (Mpa)	Weight (kg)	Max hose length	Model
	Connection Hose (1m)	N			25		0,6			30377081
	Connection Hose (1m)	N			19		0,6			30377082
	Distribution hose	G	Water high pressure	25		10	25			30371900**
	Distribution hose	Н	Water high pressure	25		10	25			30371953***
	Distribution hose	I	Water			12,5	2			30377078****
	Distribution hose	E	Water ,Food	25		12,5	2			30371898**
	Distribution hose	E	Water ,Food	18		19	2			30371897**
	Connection Hose (1m)	E	Water ,Food	10		25	2			30373663**
	Distribution hose	F	Water ,Food	25		12,5	2			30371951***
	Distribution hose	F	Water ,Food	18		19	2			30371950***
		F	Water ,Food	10		25	2			30373665***
	Distribution hose	N				19	0,6			30377080
	Distribution hose	N				25	0,6			30377079

<sup>\*</sup>Galvanised fittings \*\*With galvanized steel fittings \*\*\*With stainless steel fittings \*\*\*\*Galvanized fittings for reel 886

<sup>&</sup>lt;sup>1</sup> See table below



Hose type	Specification	Temperature range, °C	Hose fittings in free hose end, distribution hose	Hose fitting on free hose end, inlet hose	Hose connection on reel, distribution hose	Hose connection on reel, inlet hose
I	Cover and inner tube in SBR based rubber. Single steel braid	-40 - 100		Female 60° cone, chrome plated	Male 60° cone	Male 60° cone
G	Cover and inner tube in synthetic rubber. Single steel braid	-40 - 155		Female 60° cone, chrome plated	Male 60° cone	Male 60° cone
Н	Cover and inner tube in synthetic rubber. Single steel braid	-40 - 155		Female 60° cone, stainless steel	Male 60° cone	Male 60° cone
Е	Cover in NBR/PVC and inner tube in food grade quality NBR. Syntethic textile braid	-30 - 100		Female 60° cone, chrome plated	Male 60° cone	Male 60° cone
F	Cover in NBR/PVC and inner tube in food grade quality NBR. Syntethic textile braid	-20 - 100		Female 60° cone, stainless steel	Male 60° cone	Male 60° cone
N		-20 - 164				



Accessory	Part No
Pivoting Wall bracket Stainless Steel	30373668
Roller guide.	30341550
Water gun in chromium plated brass	30400110
Water gun in stainless steel 316	30400210
Water gun EX	30400211
Water gun in stainless steel 316	30400310
Air gun, standard.	30410110
Swivelling coupling 3/8(m)-3/8(m)HP	30431310
Swiv. coupling 3/8(m)-3/8(m) HP SS	30431410
Swivl. coupl.1/2(m)-3/8(f) brass	30431510
Swivl.coupl.1/2(m)-1/2(f) brass	30431610
Swivel coupling 1/2(m)- 3/4 (f) bra	30431710
Swivl. coupl. 1/2(m)-3/8(f) SS	30431810
Swivl coupl. 1/2(m)-1/2(f) SS	30431910
Swivl.coupl.1/2(m)-3/4(f) SS	30432010



