

ATEX approved stainless steel hose reel when corrosive resistance is required.



The Nederman stainless steel hose reel 886 Ex is a robust hose reel with large hose capacity for heavy duty industrial use. This hose reel is constructed for environments where high hygiene and corrosion resistance is required.

 $886\,EX$  hose reel in stainless steel is approved for use in zones 1, 2, 21 and 22 in accordance with ATEX 2014/34/EC, Equipment group II, Category 2G D.

- Unique design makes easy cleaning
- Up to 25 m (82 ft.) hose capacity
- Meets international hygienic requirement
- ATEX approved

Product name	Hose Reel 886 Ex
Connection hose length (m)	-
Type of hose	М
Media	Compressed air, Water
Colour	Stainless
Diameter, connection hose (mm)	19
Weight (kg)	31
Corrosion resistance	Stainless steel
Electric/Spring driven	Spring





Delivered with hose	Distribution hose length (m)	Distribution hose diameter (mm)	Max working pressure (Mpa)	Max hose length	Model
Yes	25	12.5	2		30804686
No		12.5	10	25	30804786
Yes	15	19	2		30804886
No		19	7,5	20	30804986

Hose type	Specification	Temperature range, °C	Hose fittings in free hose end, distribution hose	Hose fitting on free hose end, inlet hose	Hose connection on reel, distribution hose	Hose connection on reel, inlet hose
М	Cover in CR and inner tube in NBR. Synthetic textile braid. Electrically conductive	-30 - 80		Female 60° cone, stainless steel	Male 60° cone	Male 60° cone



	Accessory	Part No
	Pivoting Wall bracket Stainless Steel	30373668
	Roller guide.	30341550
	Water gun in chromium plated brass	30400110
	Water gun in stainless steel 316	30400210
	Water gun EX	30400211
	Water gun in stainless steel 316	30400310
	Air gun, standard.	30410110
4000	Swivelling coupling 3/8(m)-3/8(m)HP	30431310
4000	Swiv. coupling 3/8(m)-3/8(m) HP SS	30431410
	Swivl. coupl.1/2(m)-3/8(f) brass	30431510
	Swivl.coupl.1/2(m)-1/2(f) brass	30431610
	Swivel coupling 1/2(m)- 3/4 (f) bra	30431710
	Swivl. coupl. 1/2(m)-3/8(f) SS	30431810
	Swivl coupl. 1/2(m)-1/2(f) SS	30431910
	Swivl.coupl.1/2(m)-3/4(f) SS	30432010



