

Cable Reel C20

Functional and easy-to-use retractable power cable reel with power socket for electrical tools. IP44/IP55, cable length 12m (39 ft.), 10A.



Safe and functional high quality power cable reel with robust design in high impact composite material. The power cable reel is retractable and has an optimized spring force, ensuring that the cable retracts smoothly and evenly onto the drum.








The Nederman power cable reel C20 reel is very easy to mount, either on walls or in ceilings and is supplied with an easily mounted snap-on, pivoting wall bracket and a unique safety latch for safe and easy service of electricity. The retractable power cable reel is equally suitable for electrical tools and hand lamps and has a thermal overload protection. The cable reel C20 has a cable distribution length up to 12 m.

- Easy to mount - snap-on wall bracket
- Unique safety latch
- Drum with ball bearings on both sides
- Degree of protection code, IP44/IP55
- Rubber power cable

Product name	Cable Reel C20
Power Voltage (V)	230
Frequency (Hz)	50
No of phases	1
Amperage (A)	10
Conductors (No. x mm ²)	3Gx1,5
Media	Power
Distribution cable length (m)	12
Connection cable, Length (m)	1
Weight (kg)	4
Distribution cable, type	H07RN-F
Max Power (kW)	2,3
Max Power (kW) when cable coiled	1,4
Corrosion resistance	Standard
Electric/Spring driven	Spring




Cable Reel C20

Image	Electric plug	Colour	Connection cable (No. x mm ²)	Model
	without	Blue	3G1,5	30700220
	Euro (CEE 7/2 P+E)	Blue	3G1,5	30700420*
	UK	Blue	3G1,5	30701620**
	Euro (CEE 7/2 P+E)	Grey	3G1,5	30710420
	without	Grey	3G1,5	30710520
	Swiss SEV 1011, type 13	Grey	3Gx1,5	30721020
	Swiss SEV 1011, type 13	Blue	3Gx1,5	30724020

*Distribution cable with Euro socket and connection cable with Euro plug, IP 44.

**With UK socket, IP44, for distribution cable.

Cable Reel C20

Accessory		Part No
	Hand lamp, 230 V AC.	30420110

Cable Reel C20

