

Exhaust Hose NFC-2

High temperature hose

Specifically designed to be flexible and ductile, and to have a very low pressure drop. They are resistant to all chemicals in diesel and petrol exhaust fumes, and show high resistance to mechanical stress.



- Specifically designed to be flexible and ductile, and to have a very low pressure drop. They are resistant to all chemicals in diesel and petrol exhaust fumes, and show high resistance to mechanical stress.
- Temperature range:
Continuous use: +150 °C
Short-term use: +200 °C
- Temperature range:
Continuous use: +150 °C
Short-term use: +200 °C

| | |
|--------------|--------------------|
| Product name | Exhaust Hose NFC-2 |
| Type of hose | NFC-2 |
























Exhaust Hose NFC-2

| Diameter, hose (in) | Hose length (ft) | Model |
|---------------------|------------------|----------|
| 3 | 16 | 20825862 |
| 4 | 16 | 20825962 |
| 4 | 25 | 20826062 |
| 5 | 16 | 20826162 |
| 5 | 25 | 20826262 |
| 6 | 16 | 20826362 |
| 6 | 25 | 20826462 |

| Hose type | Specification | Temperature range, °C | Hose fittings in free hose end, distribution hose | Hose fitting on free hose end, inlet hose | Hose connection on reel, distribution hose | Hose connection on reel, inlet hose |
|-----------|---------------|---------------------------|---|---|--|-------------------------------------|
| NFC2 | | Max 150, (Short term 200) | | | | |

Exhaust Hose NFC-2

| | Accessory | Part No |
|---|--|-----------|
|  | Hose suspension, hard plastic Ø75 mm | 20373615 |
|  | Hose suspension, hard plastic Ø100 mm | 20373607 |
|  | Hose suspension, hard plastic Ø150 mm | 20373609 |
|  | Hose suspension, hard plastic Ø125 mm | 20373608 |
|  | Quick coupler 100mm (4 in) - 2 pcs | 20374641 |
|  | Connection kit 4" for quick coupler | 20375048 |
|  | Quick coupler, male, Ø100 incl. rubber sleeves and hose clip | 20375049* |
|  | Quick coupler, male, Ø150 incl. rubber sleeves and hose clip | 20376017 |
|  | Rubber sleeve, hose clamp 3"NTP,2pc | 20376474 |
|  | Rubber sleeve, hose clamp 4"NTP,2pc | 20376475 |
|  | Rubber sleeve, hose clamp 5" NTP 2pc | 20376382 |
|  | Rubber sleeve, hose clamp 6"NTP,2pc | 20376476 |
| | Y-pipe Ø100 (4 in)/100 (4 in)/100 (4 in) | 20376647 |
|  | Hose coupling 100 (4") | 20947410 |
|  | Hose coupling 125 (5") | 20948710 |
|  | Hose coupling 150 (6") | 20948810 |
|  | Hose clip with rubber sleeve, pair Ø200 | 20373838 |
|  | Reduction 200mm (8 in)-150mm (6 in) | 20374284 |
|  | Quick coupling D=100 (4") male | 20947710 |
|  | Quick coupling D=100 (4") female | 20948110 |
|  | Quick coupling D=150 (6") female | 20948310 |
|  | Quick coupling D=150 (6") male | 20947910 |

Exhaust Hose NFC-2

| | Accessory | Part No |
|---|--|-----------|
|  | Connection set 3" | 20373286 |
|  | Connection set 4" | 20373287 |
|  | Connection set 5" | 20373288 |
|  | Connection set 6" | 20373289 |
|  | Bend 4". | 20344591 |
|  | Bend 5". | 20344592 |
|  | Bend 6". | 20344593 |
|  | Hose suspension, adjustable rubber Ø100 - 150 mm | 20374530 |
|  | Adaptor for 3" hose | 20373128 |
|  | Quick safety coupler incl. rubber sleeves and hose clips, Ø100 | 20374541* |
|  | Quick safety coupler incl. rubber sleeves and hose clips, Ø150 | 20374543* |
|  | Connector 6"-5". steel. | 20344353 |
|  | Connector 5"-4". steel. | 20344354 |
|  | Connector 4"-3". steel. | 20342483 |
| | Junction pipe d=160 (6.25 in) | 20371413 |
|  | Bend 90°, Ø 200 mm (8") | 20371927 |

**Use the key ring on the one end of the coupling to more easily connect and reconnect the two hose ends or to disconnect the two hose ends.*