

QF ducting offers a complete range of diameters and accessories for easy-to-fix professional installations



Manufactured from galvanised steel or stainless steel with laser welded seams, which have smoother internal surfaces and provide greatly enhanced leak resistance, QF ducting offers an unbeatable solution for all general purpose dust extraction duties..

The Quick-Fit™ clip features a generously dimensioned sealing gasket held firmly in place by positive overcentre clamping action over the rolled collars at the duct ends to be joined. For added security, a locking pin may be inserted.

- QF for fast installation with no special tools, no painting, flexible working
- Easy to assemble installation components
- Neat slip duct connections to adapt and adjust ducting on site during installation
- Laser welded straight ducts for smoother surface and enhanced leak resistance
- Easy to extend or take apart completely for cleaning, reconfiguring or relocation

Product name	QF Duct
Material	Galvanised steel. DX51D with Z275 Coating
Operating temperature range	-20° C - 200° C
length (m)	2
Connection	QF



Image	Diameter (mm)	Thickness (mm)	Model
	80	0,7	8240020381*
	100	0,7	8240020384*
	125	0,7	8240020387*
	140	0,7	8240020390*
	150	0,7	8240020393*
	160	0,7	8240020396*
	180	0,7	8240020399*
	200	0,7	8240020402*
	224	0,7	8240020405*
	250	0,7	8240020408*
	300	0,7	8240020411*
	315	0,7	8240020414*
	350	0,7	8240020417*
	400	0,9	8240020420*
	450	0,9	8240020423**



lmage	Diameter (mm)	Thickness (mm)	Model
	500	0,9	8240020426**
	560	0,9	8240020429**
	630	0,9	8240020432**
	710	0,9	8240020435**
	100	1,25	8240020448
	125	1,25	8240020436
	140	1,25	8240020437
	125	1,25	8240020438
	160	1,25	8240020439
	180	1,25	8240020440
	200	1,25	8240020441
	224	1,25	8240020442
	250	1,25	8240020443
	300	1,25	8240020444
	315	1,25	8240020445



lmage	Diameter (mm)	Thickness (mm)	Model
==	350	1,25	8240020446
	400	1,25	8240020447
	450	1,25	8240020449
	500	1,25	8240020450
	560	1,25	8240020451
	630	1,25	8240020452
==0	710	1,25	8240020453

^{*}Welded

^{**}Lockformed