

QF Duct

QF ducting offers a complete range of diameters and accessories for easy-to-fix professional installations


















Manufactured from galvanised steel or stainless steel with laser welded seams, which have smoother internal surfaces and provide greatly enhanced leak resistance. QF ducting offers an unbeatable solution for all general purpose dust extraction duties..

The Quick-Fit™ clip features a generously dimensioned sealing gasket held firmly in place by positive overcentre clamping action over the rolled collars at the duct ends to be joined. For added security, a locking pin may be inserted.
















- QF for fast installation with no special tools, no painting, flexible working
- Easy to assemble installation components
- Neat slip duct connections to adapt and adjust ducting on site during installation
- Laser welded straight ducts for smoother surface and enhanced leak resistance
- Easy to extend or take apart completely for cleaning, reconfiguring or relocation

Nom du produit	QF Duct
Matériel	Galvanised steel. DX51D with Z275 Coating
Operating temperature range	-20° C - 200° C
Length (m)	2
Connection	QF








QF Duct

[image]	Diameter (mm)	Thickness (mm)	[model]
	80	0,7	8240020381*
	100	0,7	8240020384*
	125	0,7	8240020387*
	140	0,7	8240020390*
	150	0,7	8240020393*
	160	0,7	8240020396*
	180	0,7	8240020399*
	200	0,7	8240020402*
	224	0,7	8240020405*
	250	0,7	8240020408*
	300	0,7	8240020411*
	315	0,7	8240020414*
	350	0,7	8240020417*
	400	0,9	8240020420*
	450	0,9	8240020423**

QF Duct

[image]	Diameter (mm)	Thickness (mm)	[model]
	500	0,9	8240020426**
	560	0,9	8240020429**
	630	0,9	8240020432**
	710	0,9	8240020435**
	100	1,25	8240020448
	125	1,25	8240020436
	140	1,25	8240020437
	125	1,25	8240020438
	160	1,25	8240020439
	180	1,25	8240020440
	200	1,25	8240020441
	224	1,25	8240020442
	250	1,25	8240020443
	300	1,25	8240020444
	315	1,25	8240020445


QF Duct

[image]	Diameter (mm)	Thickness (mm)	[model]
	350	1,25	8240020446
	400	1,25	8240020447
	450	1,25	8240020449
	500	1,25	8240020450
	560	1,25	8240020451
	630	1,25	8240020452
	710	1,25	8240020453

*Welded

**Lockformed

QF Duct

	[accessory]	[partno]
	Clip P Galv 80QF Nitrile	8210000693
	Clip P Galv 100QF Nitrile	8210000694
	Clip P Galv 125QF Nitrile	8210000695
	Clip P Galv 160QF Nitrile	8210000698
	Clip P Galv 180QF Nitrile	8210000699
	Clip P Galv 200QF Nitrile	8210000700
	Clip P Galv 224QF Nitrile	8210000701
	Clip P Galv 300QF Nitrile	8210000703
	Clip P Galv 315QF Nitrile	8210000704
	Clip P Galv 350QF Nitrile	8210000705*
	Clip P Galv 400QF Nitrile	8210000706
	Clip P Galv 450QF Nitrile	8210000707
	Clip P Galv 500QF Nitrile	8210000708
	Clip P Galv 560QF Nitrile	8210000709
	Clip P Galv 140QF Nitrile	8210000696
	Clip P Galv 150QF Nitrile	8210000697
	Clip P Galv 630QF Nitrile	8210000710
	Clip P Galv 710QF Nitrile	8210000711

*Premium Clip, for tougher applications