

Industrial vacuum cleaner 306 E

Wet/dry vacuum cleaner with separator for material and liquid extraction



With a pre-separator container this wet/dry vacuum extractor is designed for extraction, collection and separation of liquids, sand, and other granules. The industrial vacuum cleaner 306E is electric powered and is suitable for wet and dry extraction. This dry/wet vacuum contains two filtration stages that ensure optimum cleaning efficiency. Suction equipment is strong and durable, suitable for building and construction industry and turning and general industries. The wet/dry vacuum containers can be easily tilted to empty their materials. The float ball prevent the first container from overflowing. The trolley is equipped with large wheels for ease of mobility.

- Easy to empty with tippable container.
- High mobility and great for handling industrial spillage.
- Liquid recovery – wet and dry extraction.

Product name	Industrial vacuum cleaner 306 E
Protection class	IP44
Installation	[Outdoor], [Indoor]
Application	[liquid], [granulate], [swarf]
Dustbin volume (l)	40 + 47 l
Max Airflow (m ³ /h)	460
Filter Area (m ²)	0,35
Power Voltage (V)	230
Frequency (Hz)	50/60
Filter type	[bag]
Number of filter elements	1
Filter material	Polyester-Teflon
Type of hose	PE/C
Max airflow (m ³ /h)	460
Noise level (dB(A))	75
Max vacuum (kPa)	-21,5
Hose length (m)	7,5
Hose diameter (mm)	51
Power (kW)	2,4



Granulate Swarf Liquid

Industrial vacuum cleaner 306 E

Description	[model]
306E - NEL3R, S50, with cyclone	42430605*
306E - NEL3R, S50, with floatball	42430606**

*Radio interference supression. With cleaning set, gulper head, scraping tool, brush and conical nozzle.

**Radio interference supression. With cleaning set

Hose type	Specification	Temperature range, °C	Hose fittings in free hose end, distribution hose	Hose fitting on free hose end, inlet hose	Hose connection on reel, distribution hose	Hose connection on reel, inlet hose
PEC		-40 Deg. C. - +60 Deg. C.				

Industrial vacuum cleaner 306 E

