

722A


Powerful dust collector with pre separator



An extremely powerful vacuum unit for the collection of blasting grit and other granulated material. The combination of high vacuum and high airflow make material transport over long distance possible. Compact design, built on a frame with the possibility of transportation by forklift. Equipped with grit and dust separator. The clean grit is collected in a silo and can be re-used. The dust is trapped in a high efficient NCF filter and discharged into a dustbin or bag.

- High vacuum and airflow
- Dust separation from grit and granulates
- Efficient self-cleaning NCF filter

Product name	722A
Installation	นอกอาคาร, ในอาคาร
Filter cleaning method	เป่าอากาศแบบไหลย้อน
Application	เมล็ด, กรวด, เศษ
Dustbin volume (l)	67+220
Filter Area (m ²)	5,25
Filter type	ไส้กรองแบบถุง
Number of filter elements	70
Noise level ((dB)A)	78.0
Weight (kg)	300
Hose length (m)	10
Hose diameter (mm)	76





เมล็ด

กรวด

เศษ



722A

รูปภาพ	Description	Filter material	Type of hose ¹	Compressed air requirement	Max airflow (m ³ /h)	Max vacuum (kPa)	รุ่น
	722A - NE96, S200 with manual discharge valve	Vyon 5,25	PU12	8,6 Nm ³ /min	660	-68	42172200*
	722A - NE76, S200 with bagholder and manual discharge valve	5,25 Vyon	-	5,4 Nm ³ /min	690	-48	42172207


*With gulper head

¹ See table below

Hose type	Specification	Temperature range, °C	Hose fittings in free hose end, distribution hose	Hose fitting on free hose end, inlet hose	Hose connection on reel, distribution hose	Hose connection on reel, inlet hose
PU12	เหมาะสำหรับวัสดุที่มีฤทธิ์กัดกร่อน ยูรีเทนใส่เสริมด้วยเหล็กเกลียวฝังตัว	- 40 deg. C. -+ 90 Deg. C.				

722A

Air powered ejectors pressure / flow diagram



Air Powered ejectors

All performance data are based on 7 bar supply pressure