Nederman

Industrial vacuum cleaner 218A

Portable dust collector for dust extraction



218A industrial vacuum cleaner is the perfect machine for collection of very fine non-explosive dust. The dry vacuums filter and cleaning system provides a long interval between filter exchange which improves the productivity.

The compressed air driven ejector creates a high airflow for excellent dust and fine powder extraction. The dust collector operates with independent air cooling for improved performance. It has an efficient cyclonic pre-separation of the dust before the filter. The robust design of the dust collector makes for a safe operation in rough condition and the big wheels makes it easy to transport. The container is easy to empty plastic dust bag is available as an option.

• perfect for very fine dust collection

· Robust design for heavy duty applications

Product name	Industrial vacuum cleaner 218A
Installation	[Indoor]
Filter cleaning method	[ReverseAirPulse]
Application	[dust], [grit], [granulate], [swarf], [fumes]
Dustbin volume (I)	47
Filter Area (m²)	1,6
Filter type	[bag]
Type of hose	[PEC]
Compressed air requirement	2,2 Nm3/min @ 7 bar
Max airflow (m³/h)	360
Noise level (dB(A))	73.5
Max vaccum (kPa)	-42
Weight (kg)	70
Hose length (m)	7,5
Hose diameter (mm)	51



This content is protected under copyright law, furnished for informational use only, and subject to change without notice. © Nederman Holding AB www.nederman.com 1



Industrial vacuum cleaner 218A

[image]	Description	[model]
	218 A - NE42	42121801

Hose type	Specification	Temperature range, °C	Hose fittings in free hose end, distribution hose	Hose fitting on free hose end, inlet hose	Hose connection on reel, distribution hose	Hose connection on reel, inlet hose
PEC		-40 Deg. C +60 Deg. C.				



Industrial vacuum cleaner 218A

	[partno]	
	Timer electrical control for ejector NE 86-96, without control box. Mounted on the compressed air connection. (Suction time: 0 - 15 min, Discharge time: 0-15 sek)	43222008
	Timer electrical control for ejector NE 22-76, without control box. Mounted on the compressed air connection. (Suction time: 0 - 15 min, Discharge time: 0-15 sek)	43220026
00	Electrical control system for ejectors NE 22-76. (Suction time: 0-5 min, Discharge time: 0-15 sek)	43220001
•	Plastic bag S50 - 25pcs 500 x 600 mm with hole for bin balancing	43650102
	Plastic bag S50 - 25pcs 630x800 mm with hole for bin balancing	43650103



Industrial vacuum cleaner 218A

