

Pneumatic pumps for grease, oil and other liquids



Ideal oil pumps for transferring low-viscosity fluids such as motor oil, old waste oil, antifreeze, transmission oil, ATF oil and other similar products. The pumps can be wall-mounted or placed directly on the drum/tank. With the aid of special accessories, many application areas can be supported.

Product name

Pneumatic oil pumps

 ϵ



Image	Description	Max working pressure (Mpa)	Inlet	Capacity	Inlet Media	Model
al F	Oilpump 3:1 for medium to heavy applications. Includes wallbracket and bung adaptor. Suction tube 180 mm long.	1	ISO-G1/4" Female	20 l/min	ISO-G1" Male	30580750
1 €	Oilpump 3:1 for medium to heavy applications. Includes wallbracket and bung adaptor. Suction tube 910 mm long.	1	ISO-G1/4" Female	20 l/min	ISO-G1" Male	30580850
¥	Oilpump 3:1 for lighter applications. With bung adaptor. Suction tube 940 mm long.	0,8	1/4" BSP Female	13 l/min	1" LP adapter	30599250
	Oilpump 5:1 for lighter applications. With bung adaptor. Suction tube 940 mm long.	0,8	1/4" BSP Female	14 l/min	1"LP adapter	30599450
Ψ	Oil Pump 5:1., High Flow for medium to heavy applications, Pump tube Ø56mm, tube length 270 mm with wall bracket	1,2	3/8" BSP Female	40 l/min	11/2" BSP Female	30599550*
	Oilpump 3:1 for lighter applications. Includes wallbracket and Ø42 mm pump tube and bung adaptor Suction tube 270 mm long.	0,8	1/4" BSP Female	12 l/min	1"LP adapter	30599150
	Oilpump 5:1 for lighter applications. With bung adaptor. Suction tube 270 mm long.	0,8	1/4" BSP Female	14 l/min	1"LP adapter	30599350
•	Oil Pump 6:1., High Flow for medium to heavy applications, Pump tube Ø50 mm, tube length 160 mm with wall bracket	1	1/4" BSP Female	23 l/min	3/4" BSP Female	39100005
	Oil Pump 6:1., High Flow for medium to heavy applications, Pump tube Ø50 mm, tube length 960 mm	1	1/4" BSP Female	23 l/min	3/4" BSP Female	39100022
### ###	Grease pump 65:1 for lighter applications. Pump tube Ø30 mm, tube length 740 mm. For 60 kg drums.	0,8	3/4" BSP Female	1000 gr/min at 6 bar		30599650
	Grease pump 65:1 for lighter applications. Pump tube Ø30 mm, tube length 940 mm. For 180 kg drums.	0,8	3/4" BSP Female	1000 gr/min at 6 bar		30599750
	Waste oil pump. Max Vacuum -95 kPa	1	1/4" BSP Female	23 l/min	1" BSP Female	30508950
	Diaphragma pump 1:1	0,8	1/4" BSP Female	60 l/min	3/4" BSP Female	30507950
	Diaphragma pump 1:1					30600050
	Kit grease pump 65:1 "Well empty" for 1/1 drum	1	1/4" BSP Female	1200 gr/min at 10 bar		30509050



Image	Description	Max working pressure (Mpa)	Inlet	Capacity	Inlet Media	Model
	Kit grease pump 65:1 "Well empty" for 1/4 drum	1	1/4" BSP Female	1200 gr/min at 10 bar		30509850
	Pneumatic piston pump 3:1 for low/medium viscosity fluids such as anti freeze windscreen liquid and chemical liquids witout tensides. Tube length 940 mm.	1	ISO-G1/4" Female	23 l/min		30581850**
	Pneumatic piston pump for wall installation 3:1 for low/medium viscosity fluids such as anti freeze windscreen liquid and chemical liquids witout tensides. Tube length 940 mm. Hose length 1600 mm.	1	ISO-G1/4" Female	24 l/min		30581950
	Grease pump 50:1 for lighter applications. Pump tube Ø30 mm, tube length 740 mm. For 20-30 kg drums.	0,8	1/4" BSP Female	800 gr/min at 6 bar		30583050
	Grease pump 50:1 for lighter applications. Pump tube Ø30 mm, tube length 480 mm. For 50-60 kg drums.	0,8	1/4" BSP Female	800 gr/min at 6 bar		30583150

^{*}Air consumption - 600l/min (0.8MPa) **Min air pressure 0,3 bar



	Accessory	Part No
*	Air Management kit	30512150
	Hosekit 1,8m, complete	30511950
	Hosekit 4m, complete	30500550
T.	Hosekit 1"	30511850
	Suction kit HP 940mm	30580950
	Suction kit LP 940mm	30581150
	Drum adaptor 42mm	30501150
	Top connection	30580650
	Extension tube 500mm	30580450
1	Extension tube 200mm	30580550
	Extension sleeve	30580350
	Foot connection	30580250
	Foot valve	30580150
	Filter	30599950
	Suctionkit 3/4"	30581650
	Wall Suctionkit with probes	30581750
*	Complete 1 1/4" filter	30594550
400	DRUM COVER Ø 350 mm 20kg	30503550
	DRUM COVER Ø 420 mm 50kg	30503650
405	DRUM COVER Ø 600 mm 180kg	30503750
	Drum cover 310mm	30593450
	FOLLOWER PLATE Ø 340	30503850



Accessory	Part No
FOLLOWER PLATE Ø 410	30503950
Follower plate Ø 585	30504050
Follower plate 310mm	30593550
Ball valve 3/8" grease	30592250