

Mobiele apparatuur voor afvalvloeistof

Mobiele smeerapparatuur voor het verwijderen van afgewerkte olie, vloeistoffen en vetten.









Handmatig gecontroleerde vatwagens en kleine mobiele tanks zijn geschikt voor de effectieve omgang van afgewerkte oliën, vloeistoffen en vetten met lage, gemiddelde en hoge viscositeit.








Product naam	Mobiele apparatuur voor afvalvloeistof
--------------	--



Mobiele apparatuur voor afvalvloeistof

Afbeelding	Naam voor Datasheet	Model
	Drainer waste oil 65l	30593150
	Waste oil drainer with wheel-mounted 90-litre tank, equipped with level gauge, collection bowl with oversize funnel, antispash screen/filter, removable tool tray.	30502250
	Combination air-operated oil suction-drainer with wheel-mounted 90-litre tank, equipped with level gauge, side collection bowl, removable tool tray.	30502350
	95 Litre Waste Oil Collection Unit for use with wall mounted pump. Complete with quick release coupling for use with optional wall mounted pump. 95 litre tank with height adjustable funnel. Level Indicator to prevent overflow.	30599850
	Air-operated combination suction-drainer with pantograph collection bowl, transparent prechamber and wheel-mounted 90-litre tank. The waste oil is drained by gravity with floor tray (14 litres) or raised for vehicles placed on an auto lift or pit, or by suction with the probes supplied. The prechamber (8-litre capacity) can be used for rapid and independent suction. Its transparency allows the quantity and quality of the sucked oil to be checked immediately. After depressurisation the drainer works independently without requiring continuous connection to the compressed air system. Suction of hot oil at 70 - 80 °C. Pantograph waste oil drainer with 90 lt. tank	30502650
	Wheel mounted floor waste oil drainer. Equipped with antispash screen which can be used as a support for draining oil filters. Also equipped with 3/4" quick connector for emptying. Dimensions 1200x600x250	30581350
	Drainer waste oil for trucks	30593250
	Pit waste oil drainer 95l. Adjustable arms 1030-1450mm. Equipped with quick release coupling	30581450
	Drainer waste oil pit mounted	30593050
	Waste oil drainer with heavy duty 1:1 diaphragm pump. 95l tank with adjustable height of the waste oil bowl. Quick couplings for compressed air supply and waste oil discharge.	30582950

Mobiele apparatuur voor afvalvloeistof

Toebehoren		Artikelnummer
	Quick connector, thread 3/4" F	30591150
	Quick connector, thread 3/4" Male	30591250
	Waste oil bowl for drum	30501950
	Quick release coupling 1" complete	30593750
	Antifreeze recovery kit	30596850