Prise clapet, KV

Prise clapet pour soudage, nettoyage et meulage.

Convient pour le soudage, le nettoyage et le meulage, lorsque les vannes automatiques ne sont pas nécessaires. Le clapet est réalisé en matière plastique conductrice.

Les kits de clapets se déclinent en quatre versions:

Pour raccordement à tuyauterie en diamètre 63 mm, montage mural sur tuyau d'aspiration

Pour raccordement à tuyauterie en diamètre 63 mm, suspendu au tuyau d'aspiration

Nom du produit	Prise clapet, KV

This content is protected under copyright law, furnished for informational use only, and subject to change without notice. © Nederman Holding AB

Prise clapet, KV

[image]	Nom de la fiche technique	Diamètre (mm)	[model]
	Vanne d'isolation avec raccord de tuyau 50 mm pour montage sur tuyau	50	40146455
	KV50 aluminium	63	40141500
	KV50	63	40146180
	KV50SP, pour montage sur cond. spiro	63	40146457
	KV50T, avec filetage		40146370
	KV50 cpl		40146450

This content is protected under copyright law, furnished for informational use only, and subject to change without notice. © Nederman Holding AB

Prise clapet, KV

[accessory]		[partno]
	Kit AS microrupteur A	40141760
	AS-set microswitch P, for KV50 cpl.	40141550

This content is protected under copyright law, furnished for informational use only, and subject to change without notice. © Nederman Holding AB