

Conduta QF em Aço Inox

Conduta QF inoxidáveis

















Manufactured from galvanised steel or stainless steel with laser welded seams, which have smoother internal surfaces and provide greatly enhanced leak resistance. QF ducting offers an unbeatable solution for all general purpose dust extraction duties.

The Quick-Fit™ clip features a generously dimensioned sealing gasket held firmly in place by positive overcentre clamping action over the rolled collars at the duct ends to be joined. For added security, a locking pin may be inserted.





- QF para instalação rápida sem ferramentas especiais, sem pintura, trabalho flexível
- Componentes de instalação fáceis de montar
- Conexões de tubos deslizantes perfeitas para adaptar e ajustar a conduta no local durante a instalação
- Tubos retos, soldados a laser para uma superfície mais lisa e maior resistência a fugas
- Fácil de instalar ou retirar completamente para limpeza, reconfiguração ou realocação

Produto	Conduta QF em Aço Inox
Material	Aço galvanizado. DX51D com revestimento Z275
Temperatura de serviço	-20° C - 200° C
Length (m)	2
Connection	QF
Thickness (mm)	0.7

Conduta QF em Aço Inox

Imagem	diâmetro (mm)	Modelo
	80	8240020721
	100	8240020724
	125	8240020727
	140	8240020730
	150	8240020733
	160	8240020736
	180	8240020739
	200	8240020742
	224	8240020745
	250	8240020748
	300	8240020751
	315	8240020754
	350	8240020757
	400	8240020760
	450	8240020763

Conduta QF em Aço Inox

Imagem	diâmetro (mm)	Modelo
	500	8240020766
	560	8240020769
	630	8240020772
	710	8240020775