# Nederman

## Suction hose PU7

#### Transparent polyurethane hose, t = 0.7. Reinforced with embedded steel helix.



Flexible hose, light weight. Suitable for use as a cleaning/suction hose and to transport abrasive material such as wood shavings, sawdust, cement dust, granulates and technical gases in the chemical and

petrochemical industries. Very good resistance to wear and ageing. Good resistance to fuels, oils, solvents and grease.

- Flexible
- Very good resistance to wear and ageing
- Good
- resistance to fuels, oils,

solvents and grease

Product name

Suction hose PU7



### Suction hose PU7

Description	Max vaccum (kPa)	Diameter (mm)	Length (m)	รุ่น
Hose PU7 Ø 38 mm Bending radius inner (40 mm)	25	38	10	40375982*
Hose PU7 Ø 51 mm Bending radius inner (35 mm)	25	51	5	40375983**
Hose PU7 Ø 51 mm Bending radius inner (35 mm)	25	51	10	40375984**
Hose PU7 Ø 63 mm Bending radius inner (60 mm)	25	63	5	40375985***
Hose PU7 Ø 63 mm Bending radius inner (60 mm)	25	63	10	40375986***
Hose PU7 Ø 76 mm Bending radius inner (70 mm)	20	76	5	40375987****
Hose PU7 Ø 76 mm Bending radius inner (70 mm)	20	76	10	40375988****
Hose PU7 Ø 152 mm Bending radius inner 150 mm)	10	152	5	40375995*****

\*Hose PU4 Ø 38 mm Max vacuum kPa at 23 ±2°C (25)

\*\*Hose  $PU4 \emptyset 38 \text{ mm}$  Max vacuum kPa at 23 ±2°C (20) \*\*\*Hose  $PU4 \emptyset 38 \text{ mm}$  Max vacuum kPa at 23 ±2°C (25) \*\*\*\*Hose  $PU4 \emptyset 63 \text{ mm}$  Max vacuum kPa at 23 ±2°C (25) \*\*\*\*Hose  $PU4 \emptyset 76 \text{ mm}$  Max vacuum kPa at 23 ±2°C (20)

\*\*\*\*\*Hose PU4 Ø 152 mm Max vacuum kPa at 23 ±2°C (10)



### Suction hose PU7

	หมายเลขขึ้นส่วน	
Q	Hose clamp 85	40903030
Q	Hose clamp 50	40903160
Q	Hose clamp 56	40903170
0	Hose clamp 75	40903180
$\bigcirc$	Hose clamp 112	40903210
	Hose clamp 104-112 ABA Robust	40903270