# Nederman

### Industrial vacuum cleaner 106 A



A high capacity vacuum unit for suction and transportation of various non-flammable liquids like oil, chemicals, mud, cooling liquids and water, as well as metal chips, sand, and other granules. The standard version vacuum unit can fill the container with liquids in a minute or two. Suction equipment is made for heavy duty work. The container is mounted to the trolley by brackets.

- Comes with NE 32 powerhead
- Wet & Dry cleaning
- Vacuuming capacity
- Easy handling
- Bottom discharge optional

Product name	Industrial vacuum cleaner 106 A			
Filter type	[bag]			
Number of filter elements	1			
Filter material	Polyester-teflon			
Type of hose	[PVC]			
Compressed air requirement	1,6 Nm3/min			
Max airflow (m³/h)	342			
Noise level (dB(A))	74.0			
Max vaccum (kPa)	-31			
Hose length (m)	7,5			
Hose diameter (mm)	51			
Note	With cleaning set, brush, conical and toothed nozzle			

CE



### Industrial vacuum cleaner 106 A

Description	[model]
106A - NE32, S50 with float ball for wet suction	42110600*

\*With cleaning set, brush, conical and toothed nozzle

Hose type	Specification	Temperature range, °C	Hose fittings in free hose end, distribution hose	Hose fitting on free hose end, inlet hose	Hose connection on reel, distribution hose	Hose connection on reel, inlet hose
PVC		- 20 deg. C. to + 70 Deg. C.				




### Industrial vacuum cleaner 106 A

	[partno]	
ð.	Electrical control system for ejectors NE 22-76. (Suction time: 0-5 min, Discharge time: 0-15 sek)	43220001
	Timer electrical control for ejector NE 22-76, without control box. Mounted on the compressed air connection. (Suction time: 0 - 15 min, Discharge time: 0-15 sek)	43220026
	Timer electrical control for ejector NE 86-96, without control box. Mounted on the compressed air connection. (Suction time: 0 - 15 min, Discharge time: 0-15 sek)	43222008



## Industrial vacuum cleaner 106 A



Air Powered ejectors

All performance data are based on 7 bar supply pressure