

## 425A

### Industrial vacuum cleaner for removal of industrial waste

---



Dual container system, designed for removal of industrial waste. This powerful suction unit comes equipped with a silo and filter container fitted with our exclusive nederman vyon self-cleaning filter ensuring the efficient filtration of large quantities of dust. The filter is cleaned automatically when the air supply is turned off. Special swivelling, locking wheels are sized to increase mobility, and make the handling of heavy loads especially simple. The unit is equipped with an adjustable counterweight valve and sack holder for discharge into sacks. The model include slots for handling by forklift.

- Dry waste suction
- Silo pre-separator with manual outlet valve
- Fork lift handling
- Sturdy trolley system with large wheels for uneven ground
- automatic filtercleaning

Nombre de producto	425A
Tipo de filtro	Cartucho
Número de elementos filtrantes	1
Tipo de manguera	PVC
Compressed air requirement	3,0 Nm <sup>3</sup> /min
Max airflow (m <sup>3</sup> /h)	342
Noise level (dB(A))	75,5
Max vaccum (kPa)	-52
Peso (kg)	119
Hose length (m)	7,5
Hose diameter (mm)	51
Aclaraciones a la ficha técnica	






## 425A

Nombre para ficha de datos	Modelo
425A - NE52	42142500

Tipo de manguera	Especificación	Rango de temperatura, °C	Acoplamiento de manguera en extremos libre, manguera de distribución	Acoplamiento de manguera en extremos libre, manguera de entrada	Manguera de conexión en enrollador, manguera de distribución	Manguera de conexión en enrollador, manguera de entrada
PVC	Máximo vacío 84kPa. Radio de curvatura interior 60mm. Reforzada con hélice de acero embebida.	- 20 deg. C. to + 70 Deg. C.				

## 425A

Accesorio		Referencia
	Control S para NE86-96	43222008
	Control S para NE 22-76	43220026
	Control S para NE 22-76	43220001

## 425A



Air Powered ejectors

All performance data are based on 7 bar supply pressure