

425A



| Product name | 425A |
|----------------------------|-------------|
| Type of hose | PVC |
| Compressed air requirement | 3,0 Nm3/min |
| Max airflow (m3/h) | 342 |
| Noise level (dB(A)) | 75,5 |
| Max vaccum (kPa) | -52 |
| Weight (kg) | 119 |
| Hose length (m) | 7,5 |
| Hose diameter (mm) | 51 |

(E



425A

| Description | วุ่น | | |
|-------------|----------|--|--|
| 425A - NE52 | 42142500 | | |

| Hose type | Specification | Temperature range, °C | Hose fittings in free hose end, distribution hose | Hose fitting on free hose end, inlet hose | Hose connection on reel, distribution hose | Hose connection on reel, inlet hose |
|-----------|---|---------------------------------|---|---|--|-------------------------------------|
| PVC | สูญญากาศแม็กซ์ 84 ก็โลปาสคาล ภายในรัศมีดัด 60mm เสริมด้วยเหล็กเกลียวฝังตัว | - 20 deg. C. to + 70 Deg. C. | | | | |



425A

Air powered ejectors pressure / flow diagram mmWC 8000 NE22 NE32 70 7000 NE42 NE52/NE54 -NE56 -NE64 NE66 4000 40 NE76 NE86 3000 30 NE96 2000 20 1000 10

400

500

600

Air Powered ejectors

All performance data are based on 7 bar supply pressure

200

300

Nm³/h

100