

410E


Industrial vacuum cleaner for removal of industrial waste materials



Dual container system, designed for removal of industrial waste. This powerful suction unit comes equipped with a silo and filter container for the removal of industrial waste materials. Special swivelling, locking wheels are sized to increase mobility, and make the handling of heavy loads simple. The silo is designed to allow the collected material to be discharged over gratings or chutes for the central collection of materials. The model include slots for handling by forklift.

- Dry waste suction
- Silo pre-separator with manual outlet valve
- Fork lift handling
- Sturdy trolley system with large wheels for uneven ground

Product naam	410E
Installatie	Binnen
Filter reinigingsmethode	Mechanisch
Applicatie	Stof, Dampen, Spaanders, Granulaten
Voltage (V)	230
Frequentie (Hz)	50
Aantal fase	1
Filtertype	Cartridge filter
Aantal filterelementen	1
Filtermateriaal	paper
Stekker	Euro (CEE 7/2 P+E)
Slangtype	PE/C
Max airflow (m ³ /h)	460
Noise level (dB(A))	75
Capacity (max airflow m ³ /h)	
Max. vacuüm	-21,5
Hose length (m)	7,5
Hose diameter (mm)	51
Vermogen (kW)	2,4
Toelichting van technische gegevens	With cleaning set, scraping tool and conical nozzle. Floor cleaning equipment is included.



Granulaten Dampen Spaanders Stof

410E

Naam voor Datasheet	[model]
410E - NEL3R, S50	42441000*

*With cleaning set, scraping tool and conical nozzle. Floor cleaning equipment is included.

Slang type	Specificaties	Temperatuurbereik, °C	Slangkoppelingen einde werkslang	Slangkoppelingen einde koppelslang	Slangaansluiting op de haspel, werkslang	Slangaansluiting op de haspel, koppelslang
PEC	Voor reinigingstoepassingen Max vacuüm 50 kPa Geleidbaarheid 10^6 Ohm	-40 Deg. C. - +60 Deg. C.				