410E

Industrial vacuum cleaner for removal of industrial waste materials

Dual container system, designed for removal of industrial waste. This powerful suction unit comes equipped with a silo and filter container for the removal of industrial waste materials. Special swivelling, locking wheels are sized to increase mobility, and make the handling of heavy loads simple. The silo is designed to allow the collected material to be discharged over gratings or chutes for the central collection of materials. The model include slots for handling by forklift.

- Dry waste suction
- Silo pre-separator with manual outlet valve
- Fork lift handling
- Sturdy trolley system with large wheels for uneven ground

Наименование товара	410E
Установка	Снаружи помещения
Метод очистки фильтра	Механическая
Применение	пыль, дым, стружка, гранулят
Напряжение (В)	230
Частота (Гц)	50
Количество фаз	1
Тип фильтра	Картриджный фильтр
Количество фильтроэлементов	1
Фильтрующий материал	paper
Электрический разъем	Euro (CEE 7/2 P+E)
Тип шланга	PE/C
Max airflow (m³/h)	460
Noise level (dB(A))	75
Capacity (max airflow m3/h)	
Max vaccum (kPa)	-21,5
Hose length (m)	7,5
Hose diameter (mm)	51
Мощность (кВт)	2,4
Пояснение к техническим данным	With cleaning set, scraping tool and conical nozzle. Floor cleaning equipment is included.

This content is protected under copyright law, furnished for informational use only, and subject to change without notice. © Nederman Holding AB

410E

Название листа технических данных	[model]
410E - NEL3R, S50	42441000*

**With cleaning set, scraping tool and conical nozzle. Floor cleaning equipment is included.*

Тип шланга	Спецификация	Температурный диапазон, °C	Фитинг на свободном конце шланга, раздаточный шланг	Фитинг на свободном конце шланга, соединительный шланг	Подключение шланга к катушке, раздаточный шланг	Подключение шланга к катушке, соединительный шланг
PEC	Для проведения уборки Макс. разрежение 50 кПа Электропроводность < 10^6 Ом	-40 Deg. C. - +60 Deg. C.				

This content is protected under copyright law, furnished for informational use only, and subject to change without notice. © Nederman Holding AB