

## Hose Reel 888 Corrosion Resistant

Medium sized open corrosion resistant hose reel.



The corrosion resistant hose reels have a stainless steel stand and swivel, brass hub, and a composite material drum, which makes them suitable in humid conditions.

Thanks to the open design, the reels are very easy to service, maintain and keep clean. The reel can be installed on wall or on the ceiling. Series 889 reels are fitted with slightly larger drums and therefore are able to take longer hoses than Series 888.



The Corrosion Resistant Reel is suitable for installations in humid conditions such as carwashes, and exposed outdoor areas. All components are manufactured in highly corrosion resistant materials.

- Easy to install and service
- Outlet position can be adjusted through 120° for optimum pull-out and pull-in angle.
- Spring power can easily be adjusted from the outside.
- Ratchet easily disengaged when required

Product name	Hose Reel 888 Corrosion Resistant
Media	Compressed air, Water, Water high pressure, Food, Alcohol and Ethanol based fluids
Connection hose length (m)	1
Delivered with hose	Yes
Colour	Black
Diameter, connection hose (mm)	10
Max hose length	
Note	Marked - Ex IIB 3GD Tx, according to ATEX directive. Hose couplings are 12mm (1/2")
Corrosion resistance	Corrosion resistance
Electric/Spring driven	Spring



# Hose Reel 888 Corrosion Resistant

















Image	Type of hose <sup>1</sup>	Media	Distribution hose length (m)	Distribution hose diameter (mm)	Max working pressure (Mpa)	Weight (kg)	Model
	B	Compressed air ,Water	15	10	1,5	16	30806288
	B	Compressed air ,Water	10	12.5	1,5	16	30806488
	G	Water high pressure	15	10	25	16	30806688
	E	Water ,Food	10	12.5	2	13	30852088
	Q	Alcohol and Ethanol based fluids	15	10	1,5	13	30806888*

\*Marked - Ex IIB 3GD Tx, according to ATEX directive. Hose couplings are 12mm (1/2")

<sup>1</sup> See table below

Hose type	Specification	Temperature range, °C	Hose fittings in free hose end, distribution hose	Hose fitting on free hose end, inlet hose	Hose connection on reel, distribution hose	Hose connection on reel, inlet hose
B	Cover in NBR/PVC and inner tube in NBR. Synthetic textile braid	-30 - 100	Male, chrome plated		Hose nipple + clip	Hose nipple 1/2 + clip
G	Cover and inner tube in synthetic rubber. Single steel braid	-40 - 155	Female 60° cone, chrome plated. With rubber hose grip	Female 60° cone, chrome plated	Male 60° cone	Male 60° cone
E	Cover in NBR/PVC and inner tube in food grade quality NBR. Synthetic textile braid	-30 - 100	Male 60° cone, chrome plated	Female 60° cone, chrome plated	Male 60° cone	Male 60° cone
Q	Cover in polyurethane and inner tube seamless polyamide. Single steel braid.	-40 to +70	Female 60° cone, stainless steel	Female 60° cone, stainless steel	Male 60° cone	Male 60° cone

## Hose Reel 888 Corrosion Resistant

	Accessory	Part No
	Roller guide.	30341550
	Pivoting bracket.	30372407
	Pivoting bracket ss.	30372408
	Water gun in chromium plated brass	30400110
	Water gun in stainless steel 316	30400210
	Water gun EX	30400211
	Water gun in stainless steel 316	30400310
	Air gun, standard.	30410110
	Swivelling coupling 3/8(m)-3/8(m)HP	30431310
	Swiv. coupling 3/8(m)-3/8(m) HP SS	30431410
	Swivl. coupl. 1/2(m)-3/8(f) brass	30431510
	Swivl. coupl. 1/2(m)-1/2(f) brass	30431610
	Swivel coupling 1/2(m)- 3/4 (f) bra	30431710
	Swivl. coupl. 1/2(m)-3/8(f) SS	30431810
	Swivl. coupl. 1/2(m)-1/2(f) SS	30431910
	Swivl. coupl. 1/2(m)-3/4(f) SS	30432010

## Hose Reel 888 Corrosion Resistant

