

## High Vacuum Nozzles

---









Nederman welding nozzles are well suited for use together with a balancing arm, but are also available with a magnetic or suction foot; see accessories below. The CWN nozzle is silenced for optimum comfort.

- 
- Designed for high vacuum without reduced performance

Product name	High Vacuum Nozzles
--------------	---------------------

## High Vacuum Nozzles





[image]	Description	[model]
	Nozzle FWN 200/50, connection D=50 mm, airflow 250 m <sup>3</sup> /h, width 200 mm	40290110*
	Nozzle FWN 400/50, connection D=50 mm, airflow 250 m <sup>3</sup> /h, width 400 mm	40290120*
	Nozzle CWN-S 105/40, connection D=40 mm, airflow 200 m <sup>3</sup> /h	40290330**
	CWN-S 105/50 nozzle silencer, connection D=50 mm, airflow 250 m <sup>3</sup> /h, suction diameter 105 mm	40290230**
	CWN-S 105/63 nozzle silencer, connection D=63 mm, airflow 400 m <sup>3</sup> /h suction diameter 105 mm	40290240**
	Nozzle CWN-S 105/50L silencer, connection D=50 mm, airflow 250 m <sup>3</sup> /h	40290270***

\*Fish tail nozzle. For mounting on balance arms, magnet or suction base. Must be combined with nozzle extension when used with balance arms.

\*\*Noise reducing nozzle. For mounting on balance arms, magnet or suction base.

\*\*\*Noise reducing nozzle with flexible steel tube extension. For mounting on balance arms, magnet or suction base.

## High Vacuum Nozzles

	[accessory]	[partno]
	Magnetic base	40290170
	Suction base	40290180
	Nozzle extension	40290200
	Sensor ring	40750020
	Handle CWN-S 105/50 & 63	40070420