

High Vacuum Nozzles









Nederman welding nozzles are well suited for use together with a balancing arm, but are also available with a magnetic or suction foot; see accessories below. The CWN nozzle is silenced for optimum comfort.

-
- Designed for high vacuum without reduced performance

Product name	High Vacuum Nozzles
--------------	---------------------

High Vacuum Nozzles





Image	Description	Model
	Nozzle FWN 200/50, connection D=50 mm, airflow 250 m ³ /h, width 200 mm	40290110*
	Nozzle FWN 400/50, connection D=50 mm, airflow 250 m ³ /h, width 400 mm	40290120*
	Nozzle CWN-S 105/40, connection D=40 mm, airflow 200 m ³ /h	40290330**
	CWN-S 105/50 nozzle silencer, connection D=50 mm, airflow 250 m ³ /h, suction diameter 105 mm	40290230**
	CWN-S 105/63 nozzle silencer, connection D=63 mm, airflow 400 m ³ /h suction diameter 105 mm	40290240**
	Nozzle CWN-S 105/50L silencer, connection D=50 mm, airflow 250 m ³ /h	40290270***

*Fish tail nozzle. For mounting on balance arms, magnet or suction base. Must be combined with nozzle extension when used with balance arms.

**Noise reducing nozzle. For mounting on balance arms, magnet or suction base.

***Noise reducing nozzle with flexible steel tube extension. For mounting on balance arms, magnet or suction base.

High Vacuum Nozzles

Accessory		Part No
	Magnetic base	40290170
	Suction base	40290180
	Nozzle extension	40290200
	Sensor ring	40750020
	Handle CWN-S 105/50 & 63	40070420