

Cartridge filter for both indoor and outdoor installations. The filter can be used for many different dust producing industries.





LCP SmartFilter is a heavy-duty multi-purpose filtration system. It is customizable to perfectly fit customer specific demands, with airflow up to 50 000 m3/h for standard version. Suitable for smoke, fumes and dust and can be used in several different applications such as welding, metal cutting and general dust and process filtration.

The new and flexible product platform allows for filter size extension also for larger scale applications. The new and innovative cartridge design - the squircle shape - utilizes the square space within the filter in the most optimal way and generates high cartridge airflow. Thus, decreasing the size and hence the footprint of the system.

Constructed with 3 mm painted steel panels, it is robust, easy to install, cost effective to ship and provides adequate corrosion protection for typical light and medium industry applications. The design is optimized for long filter lifetime providing low cost of ownership.

Insight ready control with advanced pulse cleaning logic provides for full system operation including control and monitoring, as well as gateway functionality for cloud communication.

The LCP SmartFilter has a large accessories program including; fans, dust discharge systems, inlets, outlets, bins etc. and can be equipped with package of sensors. Cartridges are available in a wide variety of materials, including antistatic and PTFE membrane.

- Gain control over filtration performance with Insight Analytics. Nederman's unique monitoring technology
- Optimized footprint through innovative cartridge design with high airflow
- Reduced TCO through intelligent cleaning system, long filter cartridge life-time and optimized footprint
- Future Proof system that is IoT prepared- Insight Ready
- Controller, HMI and Gateway all in one unit with the Insight Control Panel

Medya	LCP SmartFilter
Filtreleme kalitesi (%)	99,9
Kompresor hava tüketimi	60 litres per cleaning pulse at 6,0 bar compressed air
Kurulum	[Indoor], [Outdoor]
Materyal	3 mm epoxy-polyurethane painted sheet metal
Patlayıcı toz için ideal	False
Filtre temizlik metodu	[PulseJet]
Application	[fumes], [dust]
Çalışma Basınçı (kPa)	- 6,0 to 2,0
Çöp kovası (I)	50 or 100 (with wheels)
Filitre alanı (m²)	SC 100, 140, 141, 150, 151, 190 (54 - 840 m2) SC 178 (119 - 1848 m2) SC 179 (59 - 910 m2)



Kapasite(maks. Hava debisi m3/h)	5000 - 100000
Operating Temperature	-20 to 60 Deg. C.
Filtre türü	[cartridge]
Filtre materyali	Depending on application
Teknik bilgi onayı	Configured product









Bilgi Dökümanı ismi	[model]
LCP SmartFilter	LCP SmartFilter*

^{*}Configured product