

All-round round bag filter for demanding process and general dust application, including combustible dust applications. Suitable for both indoor and outdoor installation and available in variety of sizes and options.





LBP SmartFilter Ex is a round bag filter designed for continuous operation in many industries, for virtually every kind of process and nuisance dust, including combustible dust applications. It is customizable to perfectly fit customer specific demands, with 3 different bag lengths, filter area up to 266m2 and airflow up to approx. 30.000 m3/h (depending on duct characteristics). The new and flexible product platform allows for filter size extension also for larger scale applications. It's suitable for high dust loads, with heavy, abrasive, fibrous, sticky and agglomerating dusts. All LBP units have generously sized integral pre-separation chambers and top-to-bottom air flow direction, which reduce the load on the filter bags, improve cleaning and increase bag lifetime. Constructed with 3 mm painted steel panels, it is robust, easy to install, cost effective to ship and provides adequate corrosion protection for typical industrial applications. Trace-heating and heat insulation are also available. LBP SmartFilter has a large accessories program including; fans, dust discharge systems, inlets, outlets, bins etc., and can be equipped with package of sensors.

It has full compliance to global directives, especially important on combustible dust (ATEX) applications.

Insight ready control with advanced pulse cleaning logic provides for full system operation including control and monitoring, as well as gateway functionality for cloud communication.

- Gain control over filtration performance with Insight Analytics. Nederman's unique monitoring technology
- Reduced TCO through bag-friendly design, energy-saving and intelligent cleaning system with patented UNICLEAN solution and high-efficiency integral and standalone fans (Combifab F)
- Future Proof system that is IoT prepared- Insight Ready
- Controller, HMI and Gateway all in one unit with the Insight Control Panel

Medya	LBP SmartFilter Ex
Kurulum	[Indoor], [Outdoor]
Materyal	3 mm epoxy-polyurethane painted sheet metal
Patlayıcı toz için ideal	True
Filtre temizlik metodu	[PulseJet]
Application	[dust]
Çalışma Basınçı (kPa)	- 6,0 - 2,0
Çöp kovası (I)	50 or 100 (with wheels)
Filitre alanı (m²)	13 - 266
Kapasite(maks. Hava debisi m3/h)	Approx. 30.000
Filtre materyali	Depending on application
Ağırlık (kg)	Configured product



Dus





Bilgi Dökümanı ismi	[model]
LBP SmartFilter Ex	LBP SmartFilter Ex