

Transparent polyurethane hose, t = 1.2. Reinforced with embedded steel helix.



Application areas: Robust hose, smoothinside. Suitable for transport abrasive ofmaterial such as blasting grit, swarf and glass fibre dust. Very good resistance towear and ageing. Good resistance to fuels, oils, solvents, chemicals and grease.

- Transparent polyurethane hose, t = 1.2.
- Reinforced with embedded steel helix.
- Temp. range: -40° to +90 °C.

Product name	Suction hose PU 12
Note	Couplings included, Ø 51 mm





[image]	Description	Max vakuum (in. wg)	Diameter (in)	Length (ft)	[model]
	Hose PU12 Ø 38 L=5m	13,8	38	16	43831018
	Hose PU12 Ø 38 L=10m	13,8	38	33	43831019
	Hose PU12-38 L=20m	13,8	38	65	43831001
	Hose PU12 Ø 51 L=7,5m w. couplings	13,5	51	24	43832102*
	Hose PU12 Ø 51 L=10m w. couplers	13,5	51	33	43832200*
	Hose PU12 Ø 51 L=20m	13,5	51	65	43832300
	Hose PU12 Ø 51 L=5m	13,5	51	16	43832500
	Hose PU12 Ø 51 L=10m	13,5	51	66	43832600
					43832304
	Hose PU12 Ø 63 L=10m	10,9	63	33	43833001
	Hose PU12 Ø 63 L=20m	10,9	63	65	43833100
	Hose PU12 Ø 63 L=5m	75	63	5	43833200
	Hose PU12 Ø 76 L=10m	8,8	76	33	43834200
	Hose PU12 Ø 76 L=20m	8,8	76	65	43834300
	Hose PU12 Ø 102 L=10m	5,8	102	33	43835001



[image]	Description	Max vakuum (in. wg)	Diameter (in)	Length (ft)	[model]
	Hose PU12 Ø 152 L=10m	2,9	152	33	43836001

<sup>\*</sup>Couplings included, Ø 51 mm



[accessory]	[partno]
Hose Shelf 30M 115x70	40195450
Hose Shelf 60M 150x110	40195451
Hose Shelf 120M 200x160	40195452
Hose & Add.shelf	40196370
Hose clamp 85	40903030
Hose clamp 56	40903170
Hose clamp 75	40903180
Hose clamp 112	40903210
Hose clamp 104-112 ABA Robust	40903270