

Transparent polyurethane hose, t = 1.2. Reinforced with embedded steel helix.



Application areas: Robust hose, smooth inside. Suitable for transport abrasive of material such as blasting grit, swarf and glass fibre dust. Very good resistance to wear and ageing. Good resistance to fuels, oils, solvents, chemicals and grease.

- Transparent polyurethane hose, t = 1.2.
- Reinforced with embedded steel helix.
- Temp. range: -40° to +90 °C.

Product name	Suction hose PU 12
Note	Couplings included, Ø 51 mm





lmage	Description	Max vaccum (kPa)	Diameter (mm)	Length (m)	Model
	Hose PU12 Ø 38 L=5m	95	38	5	43831018
	Hose PU12 Ø 38 L=10m	95	38	10	43831019
	Hose PU12-38 L=20m	95	38	20	43831001
	Hose PU12 Ø 51 L=7,5m w. couplings	93	51	7,5	43832102*
	Hose PU12 Ø 51 L=10m w. couplers	93	51	10	43832200*
	Hose PU12 Ø 51 L=20m	93	51	20	43832300
	Hose PU12 Ø 51 L=5m	93	51	5	43832500
	Hose PU12 Ø 51 L=10m	93	51	10	43832600
					43832304
	Hose PU12 Ø 63 L=10m	75	63	10	43833001
	Hose PU12 Ø 63 L=20m	75	63	20	43833100
	Hose PU12 Ø 63 L=5m	75	63	5	43833200
	Hose PU12 Ø 76 L=10m	61	76	10	43834200
	Hose PU12 Ø 76 L=20m	61	76	20	43834300
	Hose PU12 Ø 102 L=10m	40	102	10	43835001



Image	Description	Max vaccum (kPa)	Diameter (mm)	Length (m)	Model
	Hose PU12 Ø 152 L=10m	20	152	10	43836001

^{*}Couplings included, Ø 51 mm



	Part No	
	Hose Shelf 30M 115x70	40195450
	Hose Shelf 60M 150x110	40195451
	Hose Shelf 120M 200x160	40195452
	Hose & Add.shelf	40196370
	Hose clamp 85	40903030
	Hose clamp 56	40903170
0	Hose clamp 75	40903180
	Hose clamp 112	40903210
	Hose clamp 104-112 ABA Robust	40903270