

## Suction hose PE

---

Application areas: Single ,mainly intended for simple cleaning.The hose is not conductive.














- Temp. range: -40° to +60 °C.
- Max. vacuum 50 kPa.

Product name	Suction hose PE
Max vakuüm (in. wg)	7,3

## Suction hose PE

[image]	Description	Diameter (in)	Length (ft)	[model]
	Hose PE Ø 25 , length 10m	25	33	40160712
	Hose PE Ø 32 , length 10m	32	32	40160722
	Hose PE Ø 38 , length 5m	38	16	40160731
	Hose PE Ø 38 , length 10m	38	33	40160733
	Hose PE Ø 38 , length 20m	38	49	40160735
	Hose PE Ø 51 , length 5m	51	16	40160741
	Hose PE Ø 32 , length 5m	32	16	40375953
	Hose PE Ø 38 , length 5m with coupling	38	5	40160370
	Hose PE Ø 50 , length 5m with coupling	50	5	40160380
	PEFA hose d51 20m			43812300
	PE hose d51 w/encd 0,75m			43812400
	PE hose d51 w/encd 1,35m			43812500

## Suction hose PE

	[accessory]	[partno]
	Hose Shelf 30M 115x70	40195450
	Hose Shelf 60M 150x110	40195451
	Hose Shelf 120M 200x160	40195452
	Hose & Add.shelf	40196370
	Hose clamp 85	40903030
	Hose clamp 56	40903170
	Hose clamp 75	40903180
	Hose clamp 112	40903210
	Hose clamp 104-112 ABA Robust	40903270
	End sleeve PE d32, antistatic	43819001
	End sleeve d38, pe, antistatic	43819011