

## Suction hose FS

---











Application areas: Flexible hose with steel helix to discharge static electricity. Mainly used for extraction from handtools and balance arms.

- Temp. range: 0 to +80 °C.
- Max. vacuum 60 kPa.












Product name	Suction hose FS
Max vacuum (kPa)	60
Length (m)	15



## Suction hose FS

Image	Description	Diameter (mm)	Model
	Hose FS-25 L=15m w.spiral	25	40160102
	Hose FS-32 L=15m w.spiral	32	40160152
	Hose FS-38 L=15m w.spiral	38	40160202
	Hose FS-44 L=15m w.spiral	44	40160223
	Hose FS-51 L=15m w.spiral	51	40160252
	Hose FS-63 L=15m w.spiral	63	40160263
	Hose FS-38 L=5m w.coupling		40160350
	Hose FS-50 L=5m w.coupling		40160360

## Suction hose FS

Accessory		Part No
	Hose Shelf 30M 115x70	40195450
	Hose Shelf 60M 150x110	40195451
	Hose Shelf 120M 200x160	40195452
	Hose & Add.shelf	40196370
	Hose clamp 85	40903030
	Hose clamp 56	40903170
	Hose clamp 75	40903180
	Hose clamp 112	40903210
	Hose clamp 104-112 ABA Robust	40903270
	Ball valve 38 typ 353 PVC cpl.	40615210
	Ballvalve for Ø44 mm hoses	40376978