

## Suction hose PVC

---







Application areas: Robust oil-resistant hose, smooth inside. Very good resistance to wear and ageing. Good resistance to fuels, oils, solvents, chemicals and grease. Technical data:

- Temp. range: -20° to +70 °C.

|                     |                  |
|---------------------|------------------|
| Product name        | Suction hose PVC |
| Max vakuum (in. wg) | 12,2             |
| Diameter (in)       | 51               |










## Suction hose PVC

| [image]   | Description  | Length (ft) | [model]    |
|---|--|-------------|------------|
|  | PVC Hose, Ø 51 mm. length 10 m with couplers             | 33          | 43822200*  |
|  | PVC Hose, Ø 51 mm. length 25 m                           | 82          | 43822300** |
|  | PVC Hose, Ø 51 mm. length 25 m with conductive couplers  | 25          | 43822301*  |
|  | PVC Hose, Ø 51 mm. length 7,5 m with conductive couplers | 25          | 43822600*  |

\*Couplings included, Ø 51 mm

\*\*Without couplers

## Suction hose PVC

| [accessory]   |                               | [partno] |
|---|-------------------------------|----------|
|    | Hose Shelf 30M 115x70         | 40195450 |
|    | Hose Shelf 60M 150x110        | 40195451 |
|    | Hose Shelf 120M 200x160       | 40195452 |
|    | Hose & Add.shelf              | 40196370 |
|    | Hose clamp 56                 | 40903170 |
|    | Hose clamp 75                 | 40903180 |
|    | Hose clamp 85                 | 40903030 |
|   | Hose clamp 112                | 40903210 |
|  | Hose clamp 104-112 ABA Robust | 40903270 |