

LBR-C SmartFilter with chain conveyor for heavy dust applications





The LBR-C is an advanced, IIoT ready, reverse air baghouse suited for continuous duty applications with high air volumes and heavy dust loading. The modular filter housing can be scaled for the required airflow and additional modules can be installed in the field if additional capacity is required. The LBR filter is self supporting with telescopic legs for height adjustment and is suitable for outdoor installations.

Air enters the filter through an inlet module or hopper inlet where the heavy / large dust particles drop out of airstream. The remaining fine particles pass through an array of highly efficient SUPERBAG filters allowing clean air to pass through. As dust accumulates on the filter bags, a regeneration fan located on each filter module blows air in the reverse direction dislodging the collected dust into the hopper where it is evacuated by the double chain conveyor to a container or material handling system.

The LBR SmartFilter features the Insight Control Panel offering complete control of the filter and system accessories. Sensors located throughout the system monitor and collect critical operational data for the local controls and can be connected to the Nederman cloud based IIoT platform for remote monitoring and system data analytics.

- Configurable. Modular design combined with a wide range of filter and system accessories allows the LBR SmartFilter to be configured to your factory's unique needs. A variety of filter sizes, depths and ability to handle either overpressure (positive) or vacuum (negative) airflow arrangement means the filter is optimized for your needs.
- Future Proof. The LBR SmartFilter controls are IIoT ready as standard, and our proprietary Insight platform enhances their current operation and prepares their factory for a digital future. Filter modules can be added in field if additional capacity is required.
- Low Operational Cost. 5-7 years of filter life, low operational pressure losses and efficient filter cleaning reduces the total cost of ownership compared to pulse jet or mechanical shaker alternatives.
- Regulatory Compliance. The LBR SmartFilter complies with the latest ATEX and NFPA combustible dust standards and regulations and our trained, experienced sales teams can provide a complete, turn-key compliant system.
- Sustainability. The LBR SmartFilter offers an energy efficient solution capable of recovering waste material to be reused or recycled.

Product name	LBR-C SmartFilter
Installation	[Outdoor]
Material	Housing in galvanised sheet

Nederman

	steel
Suitable for combustible dust	True
Filter cleaning method	Reverse air pulse
Application	[dust]
Working pressure (kPa)	5
Filter Area (m²)	Per module HJ: 85 Per module LJ: 40
Capacity (max airflow m3/h)	500000
Operating Temperature	-20 to 75°C
Power Voltage (V)	208-600
Filter type	[bag]
Filter material	Superbag 2000 XT15 with ø200 mm collar
Weight (kg)	
Power (kW)	Chain motor: 1,1 kW Regeneration fan - 1,1 kW (option 2,2 kW)
Note	Configurable product





	Model	
	LBR-C*	
*Configurable product		



Accessory	Part No
Bend 90° Complete 600 x 600	5502984
fire gate 600 x 600	5503036
Return Air ø800 End Cap	5504911
Return Air ø1000 End Cap	5504912
Return Air Duct ø1000	5504914
Return Air ø800 2xFL/800x800EP	5504915
Return Air ø1000 2xFL/800x800EP	5504916
Return Air ø800 3xFL	5504917
Return Air ø1000 3xFL	5504919
Return Air Component EP No 216	5504255
Return Air Component EP No 223	5504262
Return Air Component EP No 224	5504263
Return Air Component EP No 233	5504272
Return Air Component EP No 235	5504274
Return Air Component EP No 236	5504275
Return Air Component EP No 237	5504276
Return Air Component EP No 238	5504277
Return Air Component EP No 239	5504278
Superbag 3000 XT15 Ø200/655 For L-Filter Below Reg.Fan	5502447
Superbag 3000 XT15 Ø200/750 For Vibration Cleaning M8 X 475	5502448
Superbag 3000 XT15 Ø200/1420 For L-Filter	5502449
Superbag 3000 XT15 Ø200/1190 For Vibration Cleaning	5502450


This content is protected under copyright law, furnished for informational use only, and subject to change without notice. © Nederman Holding AB www.nederman.com 5



Accessory	Part No
Superbag 3000 XT15 Ø200/2095 For H-Filter Below Reg.Fan	5502451
Superbag 3000 XT15 Ø200/2190 For Vibration Cleaning	5502452
Superbag 3000 XT15, Ø200/2860 For H-Filter	5502453
Superbag 3000 XT15 Ø200/2630 For Vibration Cleaning	5502454

Nederman

LBR-C SmartFilter



 A #
 B
 C
 D
 E
 F
 G
 H
 I
 J**
 K**
 M
 N
 O
 P**
 Q
 R
 S
 U
 W

 2400
 1160
 245
 153
 583
 1200
 800
 3600
 720
 3420
 4230
 2321
 952
 1260
 2960
 135
 2400
 115
 150
 47

 * Optional position of outlet / reg. fan. 800 x 800 or 600 x 600 mm. (LJ version: not on door side)

 * Height of LJ version – reduce 1440 mm


 # Optional 1200 mm.

567 kg 742 kg 250 kg

L - telescopic filter legs		Туре	
Туре	Min. Adjust	Max. Adjust	J - over pressure
L= 1596	555	1250	J - vacuum
L= 2195	1155	1850	Driving station
L= 2596	1555	2250	

All dimensions in mm.





	Min. Adjust		Max. Adjust	
Туре	mm		mm	
L= 1596	555	21.85	1250	84.65
L= 2195	1155	45.47	1850	72.83
L= 2596	1555	61.22	2250	88.58