

A compact stationary high vacuum unit with high filter efficiency and enhanced flexibility and advanced features



The Nederman L-PAK offers the ideal solution for removing dust and fumes in all types of industries. Typical areas of applications can be found in welding shops, car body shops, construction industries, bakeries, industrial laundries, etc. The L-PAK is also perfect for cleaning of the workplace and the workshop floor. The L-PAK is easy to position and move due to its compact design, its low weight and the frame for fork lift handling. The integrated PLC-control ensure high functionality and can easily be updated with new functions. The automatic start/stop will save energy as well as extend the lifetime of the unit. The remote start/stop function makes it easy to ensure that everything is shut off when you go home from work.

Safe use

The duty idling and the temperature control functions reduce the risk of the fan getting overheated. There is also an indicator to show when service is required.

Unique and economic filter concept

The filter concept in L-PAK is unique as it combines high filter efficiency with long lifetime. A dynamic reducer separates coarse particles. Fine particles are separated on surface treated filter for a long lifetime. The PTFE fine filter is standard in the Advanced model but can easily be replaced by an antistatic filter if needed. You may also add a micro filter to filtrate even the finest particles.

Automatic filter cleaning as standard.

Continuous high performance is obtained by automatic filter cleaning (as standard). L-PAK uses filter cleaning by a short blast of reversed atmospheric air. By the rapid opening of a valve located on top of the filters, a powerful air pulse is created, efficiently dislodging dust from the filter socks.

Complete and ready to use

We can deliver complete installations but if you prefer to install your own system, this is very easy to do. Nederman can also offer a vast range of accessories like cleaning equipment, vacuum valves, swing arms and grinding tools with integrated fume and dust extraction.

The L-PAK Advanced models offers extra features such as improved sound insultation and enhanced functions in the PLC/control system that can handle extra external signals (DPS, BLI, pilot signal etc), adjustable cleaning cycle, start / stop timer functions etc.

- Easy to install
- Low noise level
- Low running and maintenance costs

Produkt namn	L-PAK 150 Advanced
Ljudnivå (dB(A))	62
Installation	Inomhus



	inus Rök Spån Stoft	
Effekt (kW)	3	
Utlopp	Ø100 mm	
Vikt (kg)	110	
Inlopp	Ø100 mm	
Max vaccum (kPa)	-22	
Kapacitet (max luftflöde m3/h	PTFE 290 150 at -15 kPa	
Filtermaterial Max luftflöde (m³/h)		
Antal filter	1	
Typ av filter	Påsfilter	
Faser	3	
Frekvens (Hz)	50	
Matningsspänning (V)	400	
Filterarea (m²)	15 290 1,1	
Max Luftflöde (m3/h)		
Arbetstryck (kPa)		
Metod för filterrensning Applikation	Atmosfärstrycksrensning Grus, Stoft, Rök, Spån, Granulat	




Model 40051960



	Tillbehör	Artikelnummer
	Replacement Microfilter (D=140 x 350)	40114110
	Replacement bagfilter (PTFE)	40119422
	Spirogaller dia 100 mm	40130220
0	Spiroböj BU 100 90	40130820







Kåpa som tillbehör minskar ljudet ner till 62 dB(A) för L-PAK 150 och 64 dB(A) för L-PAK 250.





Avfalls lådan av plast är lätt att byta

