

A self-contained downdraft table used for extraction and filtering of dust and odour.



The Nederman Filterbench Carbon range of downdraught benches are designed to control airborne particulate and odour arising from gluing, de-greasing, painting and similar applications. The FilterBench Carbon is available in three different sizes. Easy to use and always with extraction at hand. The FilterBench Carbon should not be used in an environment with danger of explosions or for dust in explosive concentrations. The FilterBench should not be used for hot or spark generating processes such as welding fumes or metal grinding.

- Easy to use and always with extraction at hand
- Pre-filter (G4) and carbon filters as standard
- Simple on/off push button control making the product easy to understand and operate
- Fan inverter included as standard making it possible to optimize air flow and minimize energy consumption
- Castors with swivel and brake included as standard making the product easy and safe to move and position

Produktnavn	FilterBench Downdraft Table with carbon filter
Filtereffektivitet (%)	99,9
Installasjon	Innendørs
Bruksområde	Støv, Røyk
Armlengde (m)	
Spenning (V)	230
Frekvens Hz	50
Antall faser	1
Filtermateriale	
Elektrisk plugg	Euro (CEE 7/2 P+E)
Mounting	Mobil
Filter cleaning method	Engangsfilter









Bilde	Navn på datablad	Max airflow (m³/h)	Vekt (kg)	Kraft (kW)	Model
	FilterBench 23, with carbon filter	2300	230	0,5	73000119
	FilterBench 23S, with Carbon filter	2300	280	0,5	73000538
	FilterBench 46, with carbon filter	4600	340	1	73000120
	FilterBench 69, with carbon filter	6900	470	1,5	73000121



	Artikkelnummer	
MINI	Carbon Filter 562mm x 250mm x 50mm	73000086
	Plain rubber mat 740 × 300 × 5mm	73000072
	Perforated rubber mat 740 × 770 × 5mm FB -sp	73000082
	Colourcell 562mm x 250mm x 50mm	73000087
	Prefilter G4 for FilterBench	12376528



