

## Floor cleaning system: Ø 63 mm



63 mm cleaning unit used for the heaviest applications, such as collecting blasting grit, casting sand etc. where a small pressure drop across the hose is important.

- Floor nozzle with wheels and interchangeable rubber lip
- Wet suction
- Antistatic

Product name	Floor cleaning system: Ø 63 mm
Note	ATEX: Suitable for combustible dust (zone 20,21,22). Ensure earthing to extraction unit. Not to be used in combustible gas atomspheres or extraction of explosive materials.



## Floor cleaning system: Ø 63 mm

[image]	Description	[model]
	Floor cleaning equipment with rubber lips, width 500 mm, d63 mm	42930000*
	Floor cleaning equipment with rubber lips, width 600 mm, d63 mm	42930100*

<sup>\*</sup>ATEX: Suitable for combustible dust (zone 20,21,22). Ensure earthing to extraction unit. Not to be used in combustible gas atomspheres or extraction of explosive materials.



## Floor cleaning system: Ø 63 mm

	[accessory]	[partno]
٠.	Floor suction head width 500mm, Ø63	43840400*
٠.	Floor suct head d63/600	43840450*
	Suction pipe aluminium Ø63	43843001*
-	Suct pipe bend alum d63	43843050*
	Swivel steel d63	43843100*

<sup>\*</sup>ATEX: This product is suitable to be used as cleaning equipment for combustible dusts with MIE (minimum ignition energy) >1 mJ. Product is to be properly earthed to the extraction unit. Not for usage in combustible gas atmospheres or extraction of xplosive materials.