

## Floor cleaning system: Ø 63 mm



63 mm cleaning unit used for the heaviest applications, such as collecting blasting grit, casting sand etc. where a small pressure drop across the hose is important.

- Floor nozzle with wheels and interchangeable rubber lip
- Wet suction
- Antistatic

Product name	Floor cleaning system: Ø 63 mm
Note	EX - Suitable for combustible dust with MIE (minimum ignition energy) < 1ml. Ensure earthing to extraction unit. Not to be used in combustible gas atomspheres or extraction of explosive materials



## Floor cleaning system: Ø 63 mm

Image	Description	Model
	Floor cleaning equipmentd width 500 mm	42930000*
	Floor cleaning equipment width 600 mm	42930100*

<sup>\*</sup>EX - Suitable for combustible dust with MIE (minimum ignition energy) < 1mJ. Ensure earthing to extraction unit. Not to be used in combustible gas atomspheres or extraction of explosive materials



28-04-2023

## Floor cleaning system: Ø 63 mm

Accessory		Part No
٠.	Floor suction head width 500mm, Ø63	43840400*
٠.	Floor suct head d63/600	43840450*
	Suction pipe aluminium Ø63	43843001*
-	Suct pipe bend alum d63	43843050*
	Swivel steel d63	43843100*

<sup>\*</sup>ATEX - This product is suitable to be used as cleaning equipment for combustible dusts with MIE (minimum ignition energy) >1 mJ. Product is to be properly earthed to the extraction unit. Not for usage in combustible gas atmospheres or extraction of xplosive materials.