

Fume Eliminator 860

Portable source capture for on-torch extraction



The Fume Eliminator 860 is designed to be carried to the working area. Although it can be used with a nozzle, it is specifically developed for on-torch applications - connected directly to the welding torch, it extracts the fume directly at the source. The FE 860 has a knob to set the desired suction level, an automatic start/stop function, which starts the unit as soon as the welding begins and significantly improved motor performance (versus the FE840/841).

The FE 860 is suitable for extraction of fume in maintenance welding applications and is compliant with ISO 21904 (W3).

- Portable and easy to carry.
- Automatically maintains the set extraction flow - ideal for on-torch applications
- Warnings at malfunction and when the filter is 85% and 100% full
- High efficiency Nanofiber filter protecting the user from submicron particles. F9 (EN 779) MERV 14 (ASHRAE 52.2)
- Designed for torches requiring max 18 kPa at connection point - according to ISO 21904

Medya	Fume Eliminator 860
Filtreleme kalitesi (%)	99,7
Kurulum	[Indoor]
Application	[fumes]
Çalışma Basıncı (kPa)	25
Maks. Hava debisi (m ³ /h)	180
Hose length (m)	2,5
Filtre alanı (m ²)	5,3
Güç Volt (V)	230
Frekans(Hz)	50
Faz adedi	1
Filtre türü	[cartridge]
Filtre adedi	1
Filtre materyali	Cellulose with nanofiber
Elektrik prizi	Euro (CEE 7/2 P+E)
Working pressure (kPa)	25
Ağırlık (kg)	16
Hose diameter (mm)	50
Güç (kW)	1,3
Teknik bilgi onayı	Hose outlet on the clean air side



Fumes












Fume Eliminator 860

Bilgi Dökümanı ismi	[model]
FE860 Nano 230V EU	70842010
FE860 Nano 230V EU Hose discharge	70842050*

**Hose outlet on the clean air side*

Fume Eliminator 860

[accessory]		[partno]
	Metal filtre komple, FE 840/841 için	70282004
	Metal filtre komple, FE 840/841 için	70284001
	Filter nano disposable	70377313
	Hose superflex crushproof Ø50 5m	70377340
	Hose superflex crushproof Ø50 2,5m	70377336
	Hose superflex crushproof Ø50 15m	70377339
	Kanal nozulu TM-80	70851000
	flaş nozulu PM-300	70853000
	Kanal nozulu TM-200	70854000
	Hose connection M50 Ø50	70377337