

The hose is constructed of a medium weight clear static dissipative polyurethane reinforced with a bronze coated spring steel wire helix ${\bf r}$



The static dissipative hose provides great abrasion resistance and high tear strength as well as superior chemical resistance, excellent flexibility, and tolerance for applications with wide temperature ranges (-65° F to 225° F).

• Sold in 5 lengths, examples 5', 10', 15'.



lmage	Diameter (in)	Model
	4	8010004040
	5	8010004041
	6	8010004042
	8	8010004043
	10	8010004037
	12	8010004038



Accessory	Part No
3" Bridge hose clamp	8010002517
4" Bridge hose clamp	8010002518
5" Bridge hose clamp	8010002519
6" Bridge hose clamp	8010002520
7" Bridge hose clamp	8010002521
8" Bridge hose clamp	8010002522
Adapter Hose Galv 22ga 3 QF	8040401963
Adapter Hose Galv 22ga 6 QF	8040401966
Adapter Hose Galv 22ga 7 QF	8040401967
Adapter Hose Galv 22ga 8 QF	8040401968
Adapter Hose Galv 22ga 9 QF	8040401969
Adapter Hose Galv 22ga 10 QF	8040401970
Adapter Hose Galv 22ga 11 QF	8040401971
Adapter Hose Galv 22ga 12 QF	8040401972
Adapter Hose Galv 20ga 13 QF	8040401973
Adapter Hose Galv 20ga 14 QF	8040401974
Adapter Hose Galv 20ga 15 QF	8040401975
Adapter Hose Galv 20ga 16 QF	8040401976
Adapter Hose Galv 20ga 17 QF	8040401977
Adapter Hose Galv 20ga 18 QF	8040401978
Adapter Hose Galv 20ga 19 QF	8040401979
Adapter Hose Galv 20ga 20 QF	8040401980



Accessory		Part No
	Adapter Hose Galv 20ga 21 QF	8040401981
	Adapter Hose Galv 20ga 22 QF	8040401982
	Adapter Hose Galv 20ga 23 QF	8040401983
	Adapter Hose Galv 20ga 24 QF	8040401984