

## Hose Reel 886 Acid-resistant Ex

Medium sized open acid-resistant hose reel.



In very aggressive environments such as offshore production with a high salt content in the air, or in swimming pools and baths with a high chlorine content, or in other applications with aggressive substances, there may be a risk of corrosion with normal stainless steel (AISI 304 - SS 2333). For this type of application, Nederman offers a Series 886 Ex as shown above, but with all exposed components made of acid-resistant stainless steel, (AISI 316 - SS 2343) and chemically resistant composite. Approved for installation in ATEX zones 1, 2, 21 and 22 in accordance with ATEX 2014/34/EC. Equipment category 2GD, gas group IIB.

Product name	Hose Reel 886 Acid-resistant Ex
Installation	[Outdoor], [Indoor]
Suitable for combustible dust	True
Application	[liquid]
Connection hose length (m)	1
Delivered with hose	Yes
Colour	Stainless
Weight (kg)	31
Corrosion resistance	Acid proof
Electric/Spring driven	Spring



Liquid
















## Hose Reel 886 Acid-resistant Ex

Type of hose <sup>1</sup>	Media	Distribution hose length (m)	Diameter, connection hose (mm)	Distribution hose diameter (mm)	Max working pressure (Mpa)	Model
M	Compressed air ,Water	25	10	10	2	30806086
M	Compressed air ,Water	25	12,5	12,5	2	30806286
M	Compressed air ,Water	15	19	19	2	30806486
H	Water high pressure	25	10	10	25	30806686

<sup>1</sup> See table below

Hose type	Specification	Temperature range, °C	Hose fittings in free hose end, distribution hose	Hose fitting on free hose end, inlet hose	Hose connection on reel, distribution hose	Hose connection on reel, inlet hose
M	Cover in CR and inner tube in NBR. Synthetic textile braid. Electrically conductive	-30 - 80		Female 60° cone, stainless steel	Male 60° cone	Male 60° cone
H	Cover and inner tube in synthetic rubber. Single steel braid	-40 - 155		Female 60° cone, stainless steel	Male 60° cone	Male 60° cone

## Hose Reel 886 Acid-resistant Ex

	Accessory	Part No
	Pivoting Wall bracket Stainless Steel	30373668
	Roller guide.	30341550
	Water gun in chromium plated brass	30400110
	Water gun in stainless steel 316	30400210
	Water gun EX	30400211
	Water gun in stainless steel 316	30400310
	Air gun, standard.	30410110
	Swivelling coupling 3/8(m)-3/8(m)HP	30431310
	Swiv. coupling 3/8(m)-3/8(m) HP SS	30431410
	Swivl. coupl.1/2(m)-3/8(f) brass	30431510
	Swivl.coupl.1/2(m)-1/2(f) brass	30431610
	Swivel coupling 1/2(m)- 3/4 (f) bra	30431710
	Swivl. coupl. 1/2(m)-3/8(f) SS	30431810
	Swivl coupl. 1/2(m)-1/2(f) SS	30431910
	Swivl.coupl.1/2(m)-3/4(f) SS	30432010

## Hose Reel 886 Acid-resistant Ex

