

Medium sized open acid-resistant hose reel.



In very aggressive environments such as offshore production with a high salt content in the air, or in swimming pools and baths with a high chlorine content, or in other applications with aggressive substances, there may be a risk of corrosion with normal stainless steel (AISI 304 - SS 2333). For this type of application, Nederman offers a Series 886 Ex as shown above, but with all exposed components made of acid-resistant stainless steel, (AISI 316 - SS 2343) and chemically resistant composite. Approved for installation in ATEX zones 1, 2, 21 and 22 in accordance with ATEX 2014/34/EC. Equipment category 2GD, gas group IIB.

Product name	Hose Reel 886 Acid-resistant Ex		
Connection hose length (m)	1		
Delivered with hose	[With]		
Colour	Stainless		
Weight (kg)	31		
Corrosion resistance	Acid proof		
Electric/Spring driven	Spring		





Type of hose 1	Media	Distribution hose length (m)	Diameter, connection hose (mm)	Distribution hose diameter (mm)	Max working pressure (Mpa)	[model]
M	Compressed air ,Water	25	10	10	2	30806086
M	Compressed air ,Water	25	12,5	12.5	2	30806286
M	Compressed air ,Water	15	19	19	2	30806486
Н	Water high pressure	25	10	10	25	30806686

¹ See table below

Hose type	Specification	Temperature range, °C	Hose fittings in free hose end, distribution hose	Hose fitting on free hose end, inlet hose	Hose connection on reel, distribution hose	Hose connection on reel, inlet hose
M		-30 - 80				
Н		-40 - 155				



	[accessory]	[partno]
	Pivoting Wall bracket Stainless Steel	30373668
	Roller guide.	30341550
7	Water gun in chromium plated brass	30400110
	Water gun in stainless steel	30400210
	Watergun EX	30400211
	High temperature water gun	30400310
	Air gun, standard.	30410110
4000	Swivelling coupling 3/8(m)-3/8(m)HP	30431310
4000	Swiv. coupling 3/8(m)-3/8(m) HP SS	30431410
	Swivl. coupl.1/2(m)-3/8(f) brass	30431510
	Swivl.coupl.1/2(m)-1/2(f) brass	30431610
	Swivel coupling 1/2(m)- 3/4 (f) bra	30431710
	Swivl. coupl. 1/2(m)-3/8(f) SS	30431810
	Swivl coupl. 1/2(m)-1/2(f) SS	30431910
	Swivl.coupl.1/2(m)-3/4(f) SS	30432010



