

Industrial vacuum cleaner 30 S

Economical and easy to handle three phase compact portable dust collectors



These three phase compact portable dust collectors are efficient, economical and easy to handle. The dry vacuums are very easy to dismantle and clean. The location of the (optional) micro filter prevents contamination of the pump. The forward/reverse switch saves time when moving between work sites with different phase sequence.

- Easy to handle
- High filtration efficiency
- Economical
- Micro filter as option

Product name	Industrial vacuum cleaner 30 S
Noise level (dB(A))	71
Protection class	IP55
Filter efficiency (%)	99
Installation	[Indoor]
Material	Housing in sheet metal.
Filter cleaning method	[ReverseAirPulse]
Application	[dust], [granulate], [fumes]
Dustbin volume (l)	25
Max Airflow (m3/h)	240
Hose Diameter (mm)	38
Hose length (m)	10
Power Voltage (V)	400
Frequency (Hz)	50
No of phases	3
Filter type	[bag]
Max vacuum (kPa)	
Weight (kg)	74



Granulate Fumes Dust









Industrial vacuum cleaner 30 S

[Image]	Description	Power (kW)	[model]
	30 S 400V 50Hz	3	40055800*
	30 S 400V,50Hz,antistat+micro filter	3,5	40055870**

*Includes cleaning equipment.

**Includes cleaning equipment. Antistatic filter class M and microfilter included

Industrial vacuum cleaner 30 S

	[accessory]	[partno]
	Replacement main filter	40114160
	Replacement Microfilter (D=140 x 350)	40114110
	Extended brush, 169 x 54 mm.	40190020*
	Brush hygiene, food industry	40190030*
	Round rubber brush with swivel top	40193080*
	Circular crevice nozzle in plastic. Length: 360 mm. Width: 45 x 10 mm.	40193090*
	Circular crevice nozzle in steel Length: 310 mm. Width: 55 x 15 mm	40193620**
	Rubber nozzle for confined spaces. Length: 230 mm. Width: Ø 32–38 mm.	40193130*
	Rubber nozzle for confined spaces. Length: 230 mm. Width: Ø 25–32 mm.	40193110*
	Nozzle crevice plastic 60x15 D=40	40377194

*ATEX: Suitable for combustible dust with MIE (minimum ignition energy) < 1mJ. Ensure earthing to extraction unit. Not to be used in combustible gas atmospheres or extraction of explosive materials

**ATEX: Suitable for combustible dust (zone 20,21,22) and gas (zone 1,2) of group IIA , IIB and IIC. Ensure earthing to extraction unit. Not to be used for extraction of explosive materials